



## Rotary Actuators



**Working Temperature:**  
-20°C to +80°C



**Maximum Working Pressure:**  
2.5 to 8 bar

**Media:**

Dry or lubricated compressed air, to be filtered by a 30µm filter element

**Travel Adjustment:**

±5° on the rotation 0° and 90°

### Double Acting Actuators

Tech Sheet  
10140



### Single Acting Actuators

Tech Sheet  
10141



Hydraulics

Hydraulic QRC

Pneumatic QRC

Ind. Air Prep, Monitor & Test

KELM™ Pneumatics

Pneumatic & Vacuum Equipment

Valves

Ring Main Systems

Adaptors & Fittings

Stainless Steel

Malleable Iron

Hose, Tubing & Couplings

Clamps & Clips

Sprays & Adhesives

Blow Guns & Vacuum

Wash Down & Fuelling

Air Tools

Tools, Hardware & PPE

Aluminium

0364	mm	£
KRT007DA	32	55.90
KRT012DA	40	79.80
KRT020DA	52	104.85
KRT035DA	63	96.35
KRT050DA	75	155.60
KRT075DA	83	178.40
KRT110DA	92	225.45
KRT160DA	105	270.00
KRT255DA	125	381.80
KRT435DA	140	517.20
KRT665DA	160	707.00
KRT1000DA	190	1128.90
KRT1200DA	210	1311.05
KRT1800DA	240	2199.75
KRT2700DA	270	3075.25
KRT3800DA	300	5194.15
KRT5700DA	350	7300.10

Aluminium

0364	mm	£
KRT020SRK10	52	117.70
KRT035SRK10	63	148.20
KRT050SRK10	75	178.40
KRT075SRK10	83	211.50
KRT110SRK10	92	263.00
KRT160SRK10	105	318.60
KRT255SRK10	125	457.20
KRT435SRK10	140	665.80
KRT665SRK10	160	947.25
KRT1000SRK10	190	1416.95
KRT1200SRK10	210	1662.70
KRT1800SRK10	240	2625.80
KRT2700SRK10	270	3718.30
KRT3800SRK10	300	5976.95
KRT5700SRK10	350	8402.95

For ISO Pads  
see page 687 & page 704



### Limit Switch Boxes

Captive cover bolts  
Easy mounting  
IP67

Tech Sheet  
10142



NAMUR Standard, Stainless Steel Shaft & Bracket

0364	£
KLS-820M	42.30