



## Actuated Process Ball Valves



**Actuator Working Temperature:**  
-20°C to +80°C

**Ball Valve Working Temperature:**  
-20°C to +95°C



**Actuator Working Pressure:**  
2.5 to 8 bar

**Ball Valve Maximum Working Pressure:**  
3/8" 16 bar  
1/2" to 2" 40 bar

**Actuator**

**Media:**  
Dry or lubricated compressed air, to be filtered by a 30µm filter element

**Travel Adjustment:** ±5° on the rotation 0° and 90°

**Ball Valve**  
Full Bore

### Nickel Plated Brass Body Ball Valves

Tech Sheet  
**10145**



Double Acting, Aluminium Actuator, BSPP

0364



£

2184-0000	3/8"	90.95
2184-0001	1/2"	94.25
2184-0002	3/4"	105.25
2184-0003	1"	121.70
2184-0004	1.1/4"	165.50
2184-0005	1.1/2"	227.80
2184-0006	2"	299.05

Tech Sheet  
**10146**



Single Acting, Aluminium Actuator, BSPP

0364



£

2184-0007	3/8"	152.75
2184-0008	1/2"	156.05
2184-0009	3/4"	167.05
2184-0010	1"	183.50
2184-0011	1.1/4"	227.30
2184-0012	1.1/2"	326.35
2184-0013	2"	397.60

### Nickel Plated Brass Body Ball Valves, WRAS Approved

Tech Sheet  
**10147**



Double Acting, Aluminium Actuator, BSPP

0364



£

2184-0014	1/2"	94.25
2184-0015	3/4"	105.25
2184-0016	1"	121.70
2184-0017	1.1/4"	165.50
2184-0018	1.1/2"	244.30
2184-0019	2"	315.60

Tech Sheet  
**10148**



Single Acting, Aluminium Actuator, BSPP

0364



£

2184-0020	1/2"	156.05
2184-0021	3/4"	167.05
2184-0022	1"	183.50
2184-0023	1.1/4"	227.30
2184-0024	1.1/2"	326.35
2184-0025	2"	397.60

Hydraulics

Hydraulic QRC

Pneumatic QRC

Ind. Air Prep., Monitor & Test

KELM™ Pneumatics

Pneumatic & Vacuum Equipment

Valves

Ring Main Systems

Adaptors & Fittings

Stainless Steel

Malleable Iron

Hose, Tubing & Couplings

Clamps & Clips

Sprays & Adhesives

Blow Guns & Vacuum

Wash Down & Fuelling

Air Tools

Tools, Hardware & PPE

For more Ball Valve Assemblies options, please contact our Business Development Team