



Actuated Process Ball Valves



Actuator Working Temperature:
-20°C to +80°C

Ball Valve Working Temperature:
-20°C to +200°C



Actuator Working Pressure:
2.5 to 8 bar

Ball Valve Maximum Working Pressure:
70 bar (1000psi)

Actuator

Media: Dry or lubricated compressed air, to be filtered by a 30µm filter element

Travel Adjustment: ±5° on the rotation 0° and 90°

Ball Valve
Full Bore

2 Piece Stainless Steel Body Ball Valves

Tech Sheet
10149



Double Acting, Aluminium Actuator, BSPP

0364



£

2184-0026	1/4"	102.30
2184-0027	3/8"	102.30
2184-0028	1/2"	151.20
2184-0029	3/4"	161.75
2184-0030	1"	184.30
2184-0031	1.1/4"	208.35
2184-0032	1.1/2"	248.55
2184-0033	2"	301.30

3 Piece Stainless Steel Body Ball Valves

Tech Sheet
10151



Double Acting, Aluminium Actuator, BSPP

0364



£

2184-0042	1/4"	117.10
2184-0043	3/8"	114.80
2184-0044	1/2"	128.25
2184-0045	3/4"	155.50
2184-0046	1"	205.00
2184-0047	1.1/4"	205.40
2184-0048	1.1/2"	236.90
2184-0049	2"	357.65
2184-0050	2.1/2"	765.40
2184-0051	3"	1141.75
2184-0052	4"	1669.20

Tech Sheet
10150



Single Acting, Aluminium Actuator, BSPP

0364



£

2184-0034	1/4"	164.10
2184-0035	3/8"	164.10
2184-0036	1/2"	164.10
2184-0037	3/4"	174.65
2184-0038	1"	197.20
2184-0039	1.1/4"	251.70
2184-0040	1.1/2"	291.90
2184-0041	2"	383.30

Tech Sheet
10152



Single Acting, Aluminium Actuator, BSPP

0364



£

2184-0053	1/4"	155.00
2184-0054	3/8"	152.70
2184-0055	1/2"	166.15
2184-0056	3/4"	193.40
2184-0057	1"	248.40
2184-0058	1.1/4"	248.75
2184-0059	1.1/2"	318.95
2184-0060	2"	472.80
2184-0061	2.1/2"	858.50
2184-0062	3"	1373.50
2184-0063	4"	1856.40

For more Ball Valve Assemblies options, please contact our Business Development Team