



Solenoid Valves



General Purpose 2/2 N/C, Pilot Operated Solenoid Valves

3/8"-1" WRAS Approved. EPDM Seal
1.1/2"-2" - Buna N



BSPP

Hydraulics	0030			Coil Consumption	ND (mm)	KV (L/M ³ /HR)		Replacement COIL	£
Hydraulic QRC	L182D01-38-230	3/8"	230/50	6 VA	13.5	2.5	0.35 - 16	B10AA	100.40
	L182D01-38-110	3/8"	110/50	6 VA	13.5	2.5	0.35 - 16	B10AC	100.40
	L182D01-38-2450	3/8"	24/50	6 VA	13.5	2.5	0.35 - 16	B10AE	100.40
Pneumatic QRC	L182D01-38-24	3/8"	24V DC	5.5 W	13.5	2.5	0.35 - 16	B10AL	100.40
	L182D01-12-230	1/2"	230/50	6 VA	13.5	3.8	0.35 - 16	B10AA	105.25
	L182D01-12-110	1/2"	110/50	6 VA	13.5	3.8	0.35 - 16	B10AC	105.25
	L182D01-12-2450	1/2"	24/50	6 VA	13.5	3.8	0.35 - 16	B10AE	105.25
Ind. Air Prep., Monitor & Test	L182D01-12-24	1/2"	24V DC	5.5 W	13.5	3.8	0.35 - 16	B10AL	105.25
KELIM™ Pneumatics	L182D01-34-230	3/4"	230/50	6 VA	18	5	0.35 - 12	B10AA	133.20
	L182D01-34-110	3/4"	110/50	6 VA	18	5	0.35 - 12	B10AC	133.20
	L182D01-34-2450	3/4"	24/50	6 VA	18	5	0.35 - 12	B10AE	133.20
Pneumatic & Vacuum Equipment	L182D01-34-24	3/4"	24V DC	5.5 W	18	5	0.35 - 12	B10AL	133.20
Valves	L182D01-1-230	1"	230/50	6 VA	24	12	0.35 - 12	B10AA	203.25
	L182D01-1-110	1"	110/50	6 VA	24	12	0.35 - 12	B10AC	203.25
	L182D01-1-2450	1"	24/50	6 VA	24	12	0.35 - 12	B10AE	203.25
	L182D01-1-24	1"	24V DC	5.5 W	24	12	0.35 - 12	B10AL	203.25
Ring Main Systems	L180B48-112-230	1.1/2"	230/50	14 VA	45	27	0.5 - 10	A30AA	408.90
	L180B48-112-110	1.1/2"	110/50	14 VA	45	27	0.5 - 10	A30AC	408.90
	L180B48-112-2450	1.1/2"	24/50	14 VA	45	27	0.5 - 10	A30AE	408.90
Adaptors & Fittings	L180B48-112-24	1.1/2"	24V DC	9 W	45	27	0.5 - 10	A30AL	408.90
	L180B48-2-230	2"	230/50	14 VA	45	34	0.5 - 10	A30AA	476.75
Stainless Steel	L180B48-2-110	2"	110/50	14 VA	45	34	0.5 - 10	A30AC	476.75
	L180B48-2-2450	2"	24/50	14 VA	45	34	0.5 - 10	A30AE	476.75
	L180B48-2-24	2"	24V DC	9 W	45	34	0.5 - 10	A30AL	476.75

General Purpose 2/2 N/O, Pilot Operated Solenoid Valves

Tech Sheet 1978



BSPP

Hydraulics	0030			Coil Consumption	ND (mm)	KV (L/M ³ /HR)		Replacement COIL	£
Hydraulic QRC	L282B01-38-230	3/8"	230/50	6 VA	13.5	2.5	0.35 - 12	B10AA	125.95
	L282B01-38-110	3/8"	110/50	6 VA	13.5	2.5	0.35 - 12	B10AC	125.95
	L282B01-38-2450	3/8"	24/50	6 VA	13.5	2.5	0.35 - 12	B10AE	125.95
Pneumatic QRC	L282B01-38-24	3/8"	24V DC	5.5 W	13.5	2.5	0.35 - 12	C10AL	125.95
	L282B01-12-230	1/2"	230/50	6 VA	13.5	3.8	0.35 - 12	B10AA	127.80
	L282B01-12-110	1/2"	110/50	6 VA	13.5	3.8	0.35 - 12	B10AC	127.80
	L282B01-12-2450	1/2"	24/50	6 VA	13.5	3.8	0.35 - 12	B10AE	127.80
Ind. Air Prep., Monitor & Test	L282B01-12-24	1/2"	24V DC	5.5 W	13.5	3.8	0.35 - 12	C10AL	127.80
KELIM™ Pneumatics	L282B01-34-230	3/4"	230/50	6 VA	18	5	0.35 - 12	B10AA	161.00
	L282B01-34-110	3/4"	110/50	6 VA	18	5	0.35 - 12	B10AC	161.00
	L282B01-34-2450	3/4"	24/50	6 VA	18	5	0.35 - 12	B10AE	161.00
Pneumatic & Vacuum Equipment	L282B01-34-24	3/4"	24V DC	5.5 W	18	5	0.35 - 12	C10AL	161.00
Valves	L282B01-1-230	1"	230/50	6 VA	24	12	0.35 - 12	B10AA	222.05
	L282B01-1-110	1"	110/50	6 VA	24	12	0.35 - 12	B10AC	222.05
	L282B01-1-2450	1"	24/50	6 VA	24	12	0.35 - 12	B10AE	222.05
	L282B01-1-24	1"	24V DC	5.5 W	24	12	0.35 - 12	C10AL	222.05
Ring Main Systems	L280B48-112-230	1.1/2"	230/50	14 VA	45	27	0.5 - 10	A30AA	452.90
	L280B48-112-110	1.1/2"	110/50	14 VA	45	27	0.5 - 10	A30AC	452.90
	L280B48-112-2450	1.1/2"	24/50	14 VA	45	27	0.5 - 10	A30AE	452.90
Adaptors & Fittings	L280B48-112-24	1.1/2"	24V DC	9 W	45	27	0.5 - 10	A30AL	452.90
Stainless Steel	L280B48-2-230	2"	230/50	14 VA	45	34	0.5 - 10	A30AA	511.45
	L280B48-2-110	2"	110/50	14 VA	45	34	0.5 - 10	A30AC	511.45
	L280B48-2-2450	2"	24/50	14 VA	45	34	0.5 - 10	A30AE	511.45
	L280B48-2-24	2"	24V DC	9 W	45	34	0.5 - 10	A30AL	511.45

For Reinforced PVC Braided Hose Type RPVC (to BS6066) see pages 1114-1115

