



Process Valves



NAMUR Interface Plates

For use with Omal Pneumatic valves when used in conjunction with NAMUR valves.



Aluminum

0129



KBN17030	Type 1	13.70
KBN10015	Type 2	13.70
KBN10008	Type 3	13.70

3/2 5/2 NAMUR Mount Solenoid Valves

Top face air connection. Screwdriver manual override. Protection to IP 65. Cv Factor 0.7.

Tech Sheet 10373



Valve & Coil

0030



R1518A	1/4"	230/50	95.30
R1519C	1/4"	110/50	82.65
R1520E	1/4"	24/50	82.65
R1521L	1/4"	24V DC	110.80

Stainless Steel Ball Valves, 2 Way Pneumatic Actuation, High Pressure

Working Temperature:
Actuator: -20°C to +80°C (Dry Air)
Valve: -20°C to +150°C

Tech Sheet 858



Double Acting, BSPP

0129



D400H003	3/8"	207.80
D400H004	1/2"	254.00
D400H005	3/4"	236.80
D400H006	1"	260.25
D400H007	1.1/4"	318.95
D400H008	1.1/2"	389.95
D400H009	2"	484.65

Working Temperature:
Actuator: -20°C to +80°C (Dry Air)
Valve: -20°C to +150°C

Tech Sheet 858



Single Acting, BSPP

0129



S400H003	3/8"	248.55
S400H004	1/2"	255.40
S400H005	3/4"	308.60
S400H006	1"	332.05
S400H007	1.1/4"	420.40
S400H008	1.1/2"	496.55
S400H009	2"	637.25

Hydraulics

Hydraulic QRC

Pneumatic QRC

Ind. Air Prep., Monitor & Test

KELM™ Pneumatics

Pneumatic & Vacuum Equipment

Valves

Ring Main Systems

Adaptors & Fittings

Stainless Steel

Malleable Iron

Hose, Tubing & Couplings

Clamps & Clips

Sprays & Adhesives

Blow Guns & Vacuum

Wash Down & Fuelling

Air Tools

Tools, Hardware & PPE