



# Solenoid Valves



## Stainless Steel 2/2 N/C Direct Acting Solenoid Valves

**Media:** Aggressive Media  
**Seal:** FKM  
**Body:** Stainless Steel  
**Protection Class:** IP65 (with connector fitted)

**Media Temperature:** -10°C to +130°C



Tech Sheet 10380



BSPP

0030	Coil Consumption	ND/mm	KV/L	LPM	bar	Replacement COIL	£	
FSS-18-24	1/8"	24DC	14W	3	4.5	0-8	7250	98.70
FSS-14-230	1/4"	230/50	18VA	3	4.5	0-15	7700	131.85
FSS-14-110	1/4"	110/50	18VA	3	4.5	0-15	7400	131.85
FSS-14-24	1/4"	24DC	14W	3	4.5	0-8	7250	131.85

## General Purpose 3/2 N/C Direct Acting Solenoid Valves

**Media:** Water, Oil, Air  
**Seal:** FKM  
**Body:** Brass  
**Protection Class:** IP65 (with connector fitted)

**Media Temperature:** -10°C to +130°C

Tech Sheet 10251



BSPP

0030	Coil Consumption	ND/mm	KV/L	LPM	bar	Replacement COIL	£	
F333-18-230	1/8"	230/50	18VA	2	2.2	0-10	7700	52.95
F333-18-110	1/8"	110/50	18VA	2	2.2	0-10	7400	55.00
F333-18-24	1/8"	24DC	14W	2	2.2	0-10	7250	55.00
F333-14-230	1/4"	230/50	18VA	2	2.2	0-10	7700	77.95
F333-14-110	1/4"	110/50	18VA	2	2.2	0-10	7400	77.95
F333-14-24	1/4"	24DC	14W	2	2.2	0-10	7250	77.95

## 2/2 Way Pilot Operated Valve with Assisted Lift

**Media:** Water, Oil, Air  
**Note:** Other voltages available on request

**Media Temperature:** -10°C to +130°C

Tech Sheet 10379



Compact Version, BSPP

0030	Coil Consumption	ND/mm	KV/L	LPM	bar	Replacement COIL	£	
D884DVU-230/50	1/4"	230/50	18VA	10.5	21	0-16	7700	73.70
D884DVU-110/50	1/4"	110/50	18VA	10.5	21	0-16	7400	73.70
D885DVU-230/50	3/8"	230/50	18VA	10.5	24	0-16	7700	73.70
D885DVU-24	3/8"	24DC	14W	10.5	24	0-4.5	7250	73.70
D886DVU-230/50	1/2"	230/50	18VA	10.5	25	0-16	7700	78.40
D886DVU-110/50	1/2"	110/50	18VA	10.5	25	0-16	7400	78.40
D886DVU-24	1/2"	24DC	14W	10.5	25	0-4.5	7250	78.40

Tech Sheet 10378



High Flow Version, BSPP

0030	Coil Consumption	ND/mm	KV/L	LPM	bar	Replacement COIL	£	
D288DBW-230/50	3/8"	230/50	18VA	15	60	0-16	7700	96.40
D288DBW-110/50	3/8"	110/50	18VA	15	60	0-16	7400	96.40
D288DBW-24	3/8"	24DC	14W	15	60	0-6	7250	98.05
D289BW-230/50	1/2"	230/50	18VA	15	65	0-16	7700	98.05
D289BW-110/50	1/2"	110/50	18VA	15	65	0-16	7400	98.05
D289BW-24	1/2"	24DC	14W	15	65	0-6	7250	98.05
D290DBW-230/50	3/4"	230/50	18VA	15	80	0-16	7700	143.20
D290DBW-110/50	3/4"	110/50	18VA	15	80	0-16	7400	143.20
D290DBW-24	3/4"	24DC	14W	15	80	0-6	7250	143.20
D293DBY-230/50	1"	230/50	18VA	25	170	0-16	7700	161.10
D293DBY-110/50	1"	110/50	18VA	25	170	0-16	7400	161.10
D293DBY-24	1"	24DC	14W	25	170	0-6	7250	161.10