



Solenoid Valves



Section 7 – Valves

Steam 2/2 Way N/C Steam Pilot Operated Solenoid Valves

Ambient Temperature:
-10°C to +70°C

Media Temperature:
-10°C to +180°C



Hydraulics 2/2 Way N/C, BSPP

Hydraulic QRC	0030					£
Pneumatic QRC	D634DTT24VAC	1/4"	21	0.3	10	118.35
	D634DTT110VAC	1/4"	21	0.3	10	118.35
Ind. Air Prep., Monitor & Test	D635DTT24VAC	3/8"	24	0.3	10	118.35
	D635DTT110VAC	3/8"	24	0.3	10	118.35
	D635DTT240VAC	3/8"	24	0.3	10	118.35
KELM™ Pneumatics	D636DTT24VAC	1/2"	25	0.3	10	118.35
	D636DTT110VAC	1/2"	25	0.3	10	118.35

0030					£
D636DTT240VAC	1/2"	25	0.3	10	123.10
D606DTY24VAC	3/4"	120	1	10	194.55
D606DTY110VAC	3/4"	120	1	10	194.55
D606DTY240VAC	3/4"	120	1	10	194.55
D622DTY24VAC	1"	120	1	10	194.55
D622DTY110VAC	1"	120	1	10	194.55
D622DTY240VAC	1"	120	1	10	194.55

DIN Connectors



Plug to Suit F133/F180/F280 (1/8"-1")

0030	£
2021-7303	2.70

Plug to Suit FSS/F153/F180/F280/F333 (1/8"-2")

0030	£
2021-7329	2.70

DIN Connectors with RED indicating LED



LED Plug to Suit F133/F180/F280 (1/8"-1")

0030		£
2027-5384	10V - 50V	9.70
2027-5392	70V - 250V	9.20

LED Plug to Suit FSS/F153/F180/F280/F333 (1/8"-2")

0030		£
2027-5400	10V - 50V	9.70
2027-5418	70V - 250V	9.70

Valve Coils



0030		£
2700	230/50	17.60
2400	110/50	17.60
2250	24DC	17.60
7700	230/50	24.15
7400	110/50	24.15
7250	24DC	24.15
7701	230/50	30.30
7401	110/50	30.30
7251	24DC	30.30