



Process Valves



Tech Sheet 850 & 851

Electrically Actuated, 2 Way Brass Ball Valves

Full technical specifications available on request.

- ISO 5211 Mounting Pad

Note:

The valve is suitable for non-aggressive fluids. i.e. oil, gas and light applications.

- Actuator and valve packages are available with integral fail-safe battery systems.
- IP67 Ingress Protection.
- ATEX Certification also available.

24V AC & 12V AC/DC available on request.



Working Temperature:
Actuator: -10°C to +55°C
Valve: -20°C to +150°C



Section 7 – Valves

Low Pressure, High Voltage, 100-230/50Hz, BSPP

0129		£
E100H003HV	3/8"	361.25
E100H004HV	1/2"	362.10
E100H005HV	3/4"	357.15
E100H006HV	1"	366.25
E100H007HV	1.1/4"	386.00
E100H008HV	1.1/2"	425.55
E100H009HV	2"	644.20

High Pressure, High Voltage, 100-230/50Hz, BSPP

0129			£
E101H003HV	3/8"	65	353.10
E101H004HV	1/2"	65	353.85
E101H005HV	3/4"	50	360.40
E101H006HV	1"	50	422.95
E101H007HV	1.1/4"	40	408.30
E101H008HV	1.1/2"	40	597.15
E101H009HV	2"	25	635.85
E101H010HV	2.1/2"	25	1044.45
E101H011HV	3"	25	1410.85

Low Pressure, Low Voltage, 24/50Hz - 24V DC, BSPP

0129		£
E100H003LV	3/8"	361.25
E100H004LV	1/2"	362.10
E100H005LV	3/4"	357.15
E100H006LV	1"	366.25
E100H007LV	1.1/4"	386.00
E100H008LV	1.1/2"	425.55
E100H009LV	2"	644.20

High Pressure, Low Voltage, 24/50Hz - 24V DC, BSPP

0129			£
E101H003LV	3/8"	65	353.10
E101H004LV	1/2"	65	353.85
E101H005LV	3/4"	50	360.40
E101H006LV	1"	50	422.95
E101H007LV	1.1/4"	40	408.30
E101H008LV	1.1/2"	40	597.15
E101H009LV	2"	25	631.50
E101H010LV	2.1/2"	25	1044.45
E101H011LV	3"	25	1288.45

Tech Sheet 852

Electrically Actuated, 3 Way L Ported Brass Ball Valves

Full technical specifications available on request.

- ISO 5211 Mounting Pad

Note:

The valve is suitable for non-aggressive fluids. i.e. oil, gas and light applications.

- Actuator and valve packages are available with integral fail-safe battery systems.
- IP67 Ingress Protection.
- ATEX Certification also available.

24V AC & 12V AC/DC available on request.



Working Temperature:
Actuator: -10°C to +55°C
Valve: -20°C to +150°C



Low Pressure, High Voltage, 100-230/50Hz, BSPP

0129		£
E153H003HV	3/8"	367.05
E153H004HV	1/2"	367.85
E153H005HV	3/4"	378.55
E153H006HV	1"	415.70
E153H007HV	1.1/4"	470.95
E153H008HV	1.1/2"	672.20
E153H009HV	2"	761.80

Low Pressure, Low Voltage, 24/50Hz - 24V DC, BSPP

0129		£
E153H003LV	3/8"	367.05
E153H004LV	1/2"	367.85
E153H005LV	3/4"	378.55
E153H006LV	1"	415.70
E153H007LV	1.1/4"	470.95
E153H008LV	1.1/2"	672.20
E153H009LV	2"	761.80