



Pneumatic Actuated Valves



Pneumatic Actuated Stainless Steel 3 Way Valves

Seats: PTFE
Seals: PTFE
Threads: BSPP



Working Pressure:
1000 psi W.O.G.



Double Acting, L Ported, BSPP

0030		£
DA-1/4LSS	1/4"	276.65
DA-3/8LSS	3/8"	276.65
DA-1/2LSS	1/2"	287.50
DA-3/4LSS	3/4"	385.95
DA-1LSS	1"	415.00
DA-11/4LSS	1.1/4"	484.00
DA-11/2LSS	1.1/2"	646.25
DA-2LSS	2"	798.70

Double Acting, T Ported, BSPP

0030		£
DA-1/4TSS	1/4"	276.65
DA-3/8TSS	3/8"	276.65
DA-1/2TSS	1/2"	287.50
DA-3/4TSS	3/4"	385.95
DA-1TSS	1"	447.30
DA-11/4TSS	1.1/4"	484.00
DA-11/2TSS	1.1/2"	646.25
DA-2TSS	2"	798.70

Single Acting, L Ported, BSPP

0030		£
SA-1/4LSS	1/4"	317.00
SA-3/8LSS	3/8"	317.00
SA-1/2LSS	1/2"	327.90
SA-3/4LSS	3/4"	435.35
SA-1LSS	1"	464.40
SA-11/4LSS	1.1/4"	533.35
SA-11/2LSS	1.1/2"	701.30
SA-2LSS	2"	853.80

Single Acting, T Ported, BSPP

0030		£
SA-1/4TSS	1/4"	317.00
SA-3/8TSS	3/8"	317.00
SA-1/2TSS	1/2"	327.90
SA-3/4TSS	3/4"	435.35
SA-1TSS	1"	480.80
SA-11/4TSS	1.1/4"	533.35
SA-11/2TSS	1.1/2"	701.30
SA-2TSS	2"	853.80

Pneumatic Actuated Stainless Steel 2 Piece, 2 Way Ball Valves

Valve: 2 piece full bore ball valve, stainless steel body BSP female threads.

Actuator: Rilsan coated aluminium body, 1/4" BSP female ports.

Suitable Media: Hot Water, Gasoline, Unleaded Gasoline, Fuel, Gas-Oil, Oils, Compressed Air.

Not suitable for methyl alcohol & saturated steam.

Actuator assembly based on 6 bar pilot air.

Other end connections on request:

Socket Weld, Butt Weld, NPT.

Stainless Actuator available on request.

Working Temperature:
-20°C to +80°C



Double Acting Actuation, BSPP

0030		£
DA-1/4SS2	1/4"	242.25
DA-3/8SS2	3/8"	242.25
DA-1/2SS2	1/2"	224.10
DA-3/4SS2	3/4"	231.35
DA-1SS2	1"	253.10
DA-11/4SS2	1.1/4"	282.15
DA-11/2SS2	1.1/2"	377.80
DA-2SS2	2"	482.00

Single Acting Actuation, BSPP

0030		£
SA-1/4SS2	1/4"	282.60
SA-3/8SS2	3/8"	282.60
SA-1/2SS2	1/2"	264.45
SA-3/4SS2	3/4"	321.90
SA-1SS2	1"	343.70
SA-11/4SS2	1.1/4"	435.45
SA-11/2SS2	1.1/2"	489.90
SA-2SS2	2"	577.10

Pneumatic Actuated Stainless Steel High Pressure Valves

Seats: PTFE/PVDF
Seals: RTFE

Threads: BSPP (others available on request)

Working Pressure:
6000 psi/408 bar



Double Acting Actuation, BSPP

0030		£
DA-1/4SSHP	1/4"	460.60
DA-3/8SSHP	3/8"	464.10
DA-1/2SSHP	1/2"	468.70
DA-3/4SSHP	3/4"	531.80
DA-1SSHP	1"	667.75

Single Acting Actuation, Spring Return, BSPP

0030		£
SA-1/4SSHP	1/4"	495.70
SA-3/8SSHP	3/8"	499.20
SA-1/2SSHP	1/2"	503.80
SA-3/4SSHP	3/4"	610.55
SA-1SSHP	1"	765.20

For ISO 5211 Ball Valve see page 687



Hydraulics

Hydraulic QRC

Pneumatic QRC

Ind. Air Prep., Monitor & Test

KELM™ Pneumatics

Pneumatic & Vacuum Equipment

Valves

Ring Main Systems

Adaptors & Fittings

Stainless Steel

Malleable Iron

Hose, Tubing & Couplings

Clamps & Clips

Sprays & Adhesives

Blow Guns & Vacuum

Wash Down & Fuelling

Air Tools

Tools, Hardware & PPE