



Butterfly Wafer Pattern Valves

HUK valves

Cast Iron Body, Ductile Iron Disc, EPDM Liner

Suitable for Flanges: BS10 Table E, PN10/16, ANSI150.

Temperature Range: -30°C to +130°C



Tech Sheet 14

Lever Operated

0030	Flange Size	£
LEVER/50DIEP	2"	58.70
LEVER/65DIEP	2.1/2"	66.60
LEVER/80DIEP	3"	74.60
LEVER/100DIEP	4"	98.35
LEVER/125DIEP	5"	122.20
LEVER/150DIEP	6"	158.65
LEVER/200DIEP	8"	218.95
LEVER/250DIEP	10"	364.90

Suitable for Flanges: BS10 Table E, PN10/16, ANSI150.

Temperature Range: -30°C to +130°C



Tech Sheet 14

Gear Operated

0030	Flange Size	£
GEAR/50DIEP	2"	112.65
GEAR/65DIEP	2.1/2"	117.40
GEAR/80DIEP	3"	125.35
GEAR/100DIEP	4"	149.10
GEAR/125DIEP	5"	172.90
GEAR/150DIEP	6"	202.70
GEAR/200DIEP	8"	298.25
GEAR/250DIEP	10"	444.25
GEAR/300DIEP	12"	625.10

Suitable for Flanges: BS10 Table E, PN10/16, ANSI150.

Temperature Range: -30°C to +130°C



Tech Sheet 15

Pneumatic Single Acting

0030	Flange Size	£
SA/50DIEP	2"	360.05
SA/65DIEP	2.1/2"	409.50
SA/80DIEP	3"	493.50
SA/100DIEP	4"	588.70
SA/125DIEP	5"	841.40
SA/150DIEP	6"	1186.20
SA/200DIEP	8"	2308.50
SA/250DIEP	10"	2409.80
SA/300DIEP	12"	4341.90

Temperature Range: -30°C to +130°C

Tech Sheet 16

Actuator: Rilsan Coated Aluminium Body, 1/4" BSP Female Ports. Suitable for Flanges: BS10 Table E, PN10/16, ANSI150. Actuator assembly based on 6 bar Pilot Air.

Pneumatic Double Acting

0030	Flange Size	£
DA/50DIEP	2"	247.95
DA/65DIEP	2.1/2"	314.40
DA/80DIEP	3"	320.90
DA/100DIEP	4"	381.00
DA/125DIEP	5"	479.10
DA/150DIEP	6"	537.95
DA/200DIEP	8"	779.20
DA/250DIEP	10"	1109.90
DA/300DIEP	12"	2278.60

Electric Actuator Safe Area 85 - 240V AC or DC single Phase (10" and 12" 230V AC Only). Suitable for Flanges: PN16 (ANSI150 on request).

Battery Backup Failsafe and Modulating (4-20mA or 0-10V) on request. ATEX Approved Actuator on request.

Temperature Range: -30°C to +130°C



Tech Sheet 17

Electric Actuated, High Voltage

0030	Flange Size	£
E/50DIEP-HV	2"	494.35
E/65DIEP-HV	2.1/2"	602.80
E/80DIEP-HV	3"	774.30
E/100DIEP-HV	4"	1021.65
E/125DIEP-HV	5"	1456.90
E/150DIEP-HV	6"	1466.70
E/200DIEP-HV	8"	1696.60
E/250DIEP-HV	10"	2895.95
E/300DIEP-HV	12"	4425.75

Suitable for Flanges: BS10 Table E, PN10/16, ANSI150.

Temperature Range: -30°C to +130°C

Tech Sheet 17

Electric Actuated, Low Voltage

0030	Flange Size	£
E/50DIEP-LV	2"	494.35
E/65DIEP-LV	2.1/2"	602.80
E/80DIEP-LV	3"	774.30
E/100DIEP-LV	4"	1021.65
E/125DIEP-LV	5"	1456.90
E/150DIEP-LV	6"	1466.70
E/200DIEP-LV	8"	1696.60

For Stainless Steel Ball Valves see page 703



Hydraulics

Hydraulic QRC

Pneumatic QRC

Ind. Air Prep, Monitor & Test

KELM™ Pneumatics

Pneumatic & Vacuum Equipment

Valves

Ring Main Systems

Adaptors & Fittings

Stainless Steel

Malleable Iron

Hose, Tubing & Couplings

Clamps & Clips

Sprays & Adhesives

Blow Guns & Vacuum

Wash Down & Fuelling

Air Tools

Tools, Hardware & PPE