



## Butterfly Wafer Pattern Valves

### HUK valves

### Cast Iron Body, Stainless Steel Disc, Silicon Liner

Suitable for Flanges: BS10 Table E, PN10/16, ANSI150.

Temperature Range: -40°C to +200°C



Tech Sheet 14

Lever Operated

0030	Flange Size	£
LEVER/50SSSIL	2"	467.95
LEVER/65SSSIL	2.1/2"	512.80
LEVER/80SSSIL	3"	649.70
LEVER/100SSSIL	4"	1067.40
LEVER/125SSSIL	5"	1463.95
LEVER/150SSSIL	6"	1564.05
LEVER/200SSSIL	8"	1921.45
LEVER/250SSSIL	10"	3463.25

Suitable for Flanges: BS10 Table E, PN10/16, ANSI150.

Temperature Range: -40°C to +200°C



Tech Sheet 14

Gear Operated

0030	Flange Size	£
GEAR/50SSSIL	2"	467.95
GEAR/65SSSIL	2.1/2"	512.80
GEAR/80SSSIL	3"	649.70
GEAR/100SSSIL	4"	1067.40
GEAR/125SSSIL	5"	1463.95
GEAR/150SSSIL	6"	1564.05
GEAR/200SSSIL	8"	1921.45
GEAR/250SSSIL	10"	3463.25
GEAR/300SSSIL	12"	4086.95

Suitable for Flanges: BS10 Table E, PN10/16, ANSI150.

Temperature Range: -40°C to +200°C



Tech Sheet 15

Pneumatic Single Acting

0030	Flange Size	£
SA/50SSSIL	2"	467.95
SA/65SSSIL	2.1/2"	512.80
SA/80SSSIL	3"	649.70
SA/100SSSIL	4"	1067.40
SA/125SSSIL	5"	1463.95
SA/150SSSIL	6"	1564.05
SA/200SSSIL	8"	1921.45
SA/250SSSIL	10"	3463.25
SA/300SSSIL	12"	4086.95

Temperature Range: -40°C to +200°C

Tech Sheet 16

Actuator: Rilsan Coated Aluminium Body, 1/4" BSP Female Ports. BS10 Table E, PN10/16, ANSI150. Actuator assembly based on 6 bar Pilot Air.

Suitable for Flanges:

Pneumatic Double Acting

0030	Flange Size	£
DA/50SSSIL	2"	374.25
DA/65SSSIL	2.1/2"	463.35
DA/80SSSIL	3"	516.95
DA/100SSSIL	4"	645.20
DA/125SSSIL	5"	851.20
DA/150SSSIL	6"	1008.15
DA/200SSSIL	8"	1486.45
DA/250SSSIL	10"	2199.00
DA/300SSSIL	12"	3466.00

Electric Actuator Safe Area 85 - 240V AC or DC single Phase (10" and 12" 230V AC Only).

Suitable for Flanges: PN10/16, ANSI150 & BS10 Table E.

Temperature Range: -40°C to +200°C

Battery Backup Failsafe and Modulating (4-20mA or 0-10V) on request. ATEX Approved Actuator on request.



Tech Sheet 17

Electric Actuated, High Voltage

0030	Flange Size	£
E/50SSSIL-HV	2"	620.65
E/65SSSIL-HV	2.1/2"	751.75
E/80SSSIL-HV	3"	970.40
E/100SSSIL-HV	4"	1285.80
E/125SSSIL-HV	5"	1829.05
E/150SSSIL-HV	6"	1936.90
E/200SSSIL-HV	8"	2403.85
E/250SSSIL-HV	10"	3985.05

Suitable for Flanges: BS10 Table E, PN10/16, ANSI150.

Temperature Range: -40°C to +200°C

Tech Sheet 17

Electric Actuated, Low Voltage

0030	Flange Size	£
E/50SSSIL-LV	2"	467.95
E/65SSSIL-LV	2.1/2"	512.80
E/80SSSIL-LV	3"	649.70
E/100SSSIL-LV	4"	1067.40
E/125SSSIL-LV	5"	1463.95
E/150SSSIL-LV	6"	1564.05
E/200SSSIL-LV	8"	1921.45

## For Plastic Hose Reels see page 1193



### CONAH

Hydraulics

Hydraulic QRC

Pneumatic QRC

Ind. Air Prep, Monitor & Test

KELM™ Pneumatics

Pneumatic & Vacuum Equipment

Valves

Ring Main Systems

Adaptors & Fittings

Stainless Steel

Malleable Iron

Hose, Tubing & Couplings

Clamps & Clips

Sprays & Adhesives

Blow Guns & Vacuum

Wash Down & Fuelling

Air Tools

Tools, Hardware & PPE