



Butterfly Wafer Pattern Valves

HUK valves

Cast Iron Body Stainless Steel Disc, EPDM Liner

Suitable for Flanges: PN16 (ANSI150 on request).
• Gear box on request.

Temperature Range:
-30°C to +130°C



Tech Sheet
14

Lever Operated

0030	Flange Size	£
L/LEVER/40SSEP	1.1/2"	77.65
L/LEVER/50SSEP	2"	78.30
L/LEVER/65SSEP	2.1/2"	92.40
L/LEVER/80SSEP	3"	104.85
L/LEVER/100SSEP	4"	145.20
L/LEVER/125SSEP	5"	193.15
L/LEVER/150SSEP	6"	224.40
L/LEVER/200SSEP	8"	402.25
L/LEVER/250SSEP	10"	662.45

Actuator: Rilsan Coated Aluminium Body, 1/4" BSP Female Ports.
Suitable for Flanges: PN16 (ANSI150 on request).

Temperature Range:
-30°C to +130°C



Tech Sheet
15

Pneumatic Single Acting

0030	Flange Size	£
L/SA/50SSEP	2"	395.80
L/SA/65SSEP	2.1/2"	449.95
L/SA/80SSEP	3"	539.85
L/SA/100SSEP	4"	642.50
L/SA/125SSEP	5"	908.10
L/SA/150SSEP	6"	1274.40
L/SA/200SSEP	8"	2509.15
L/SA/250SSEP	10"	2769.35
L/SA/300SSEP	12"	4940.50

Actuator: Rilsan Coated Aluminium Body, 1/4" BSP Female Ports.
Suitable for Flanges: PN16 (ANSI150 on request).

Temperature Range:
-30°C to +130°C

Pneumatic Double Acting

0030	Flange Size	£
L/DA/50SSEP	2"	283.70
L/DA/65SSEP	2.1/2"	354.80
L/DA/80SSEP	3"	367.25
L/DA/100SSEP	4"	434.85
L/DA/125SSEP	5"	546.10
L/DA/150SSEP	6"	626.45
L/DA/200SSEP	8"	980.30
L/DA/250SSEP	10"	1469.90
L/DA/300SSEP	12"	2877.20

Actuator assembly based on 6 bar Pilot Air.

Tech Sheet
16

Electric Actuator Safe Area 85 - 240V AC or DC single Phase (10" and 12" 230V AC Only).
Suitable for Flanges: PN16 (ANSI150 on request).

Temperature Range:
-30°C to +130°C



Tech Sheet
17

Electric Actuated, High Voltage

0030	Flange Size	£
L/E/50SSEP-HV	2"	530.10
L/E/65SSEP-HV	2.1/2"	643.20
L/E/80SSEP-HV	3"	820.65
L/E/100SSEP-HV	4"	1075.50
L/E/125SSEP-HV	5"	1523.65
L/E/150SSEP-HV	6"	1554.90
L/E/200SSEP-HV	8"	1897.75
L/E/250SSEP-HV	10"	3255.35
L/E/300SSEP-HV	12"	5024.20

Electric Actuator Safe Area 12-24V AC or DC single Phase (10" and 12" 24V AC/DC Only).
Suitable for Flanges: PN16 (ANSI150 on request).

Temperature Range:
-30°C to +130°C

Electric Actuated, Low Voltage

0030	Flange Size	£
L/E/50SSEP-LV	2"	530.10
L/E/65SSEP-LV	2.1/2"	643.20
L/E/80SSEP-LV	3"	820.65
L/E/100SSEP-LV	4"	1075.50
L/E/125SSEP-LV	5"	1523.65
L/E/150SSEP-LV	6"	1554.90
L/E/200SSEP-LV	8"	1897.75

request).
Battery Backup Failsafe and Modulating (4-20mA or 0-10V) on request.
ATEX Approved Actuator on request.

Tech Sheet
17



For Layflat Delivery Hose

see page 1156



Hydraulics

Hydraulic QRC

Pneumatic QRC

Ind. Air Prep., Monitor & Test

KELM™ Pneumatics

Pneumatic & Vacuum Equipment

Valves

Ring Main Systems

Adaptors & Fittings

Stainless Steel

Malleable Iron

Hose, Tubing & Couplings

Clamps & Clips

Sprays & Adhesives

Blow Guns & Vacuum

Wash Down & Fuelling

Air Tools

Tools, Hardware & PPE