



Component Parts



Threaded Plugs

• Captive NBR Seal.

Tech Sheet 1656



BSPP

0350



£

VSR1/8WD	1/8"	2.85
VSR1/4WD	1/4"	3.30
VSR3/8WD	3/8"	3.90
VSR1/2WD	1/2"	5.50
VSR3/4WD	3/4"	7.05
VSR1WD	1"	13.60
VSR11/4WD	1.1/4"	23.10
VSR11/2WD	1.1/2"	26.40

• Captive NBR Seal.

Tech Sheet 1656



Metric

0350



£

VSM8X1.0WD	M8 x 1.0	4.40
VSM12X1.5WD	M12 x 1.5	4.75
VSM14X1.5WD	M14 x 1.5	5.30
VSM16X1.5WD	M16 x 1.5	6.25
VSM18X1.5WD	M18 x 1.5	6.25
VSM20X1.5WD	M20 x 1.5	8.50
VSM22X1.5WD	M22 x 1.5	7.90
VSM26X1.5WD	M26 x 1.5	11.70
VSM27X2WD	M27 x 2	10.25
VSM33X2WD	M33 x 2	13.60
VSM42X2WD	M42 x 2	19.70
VSM48X2WD	M48 x 2	27.10

Blanking Plugs

Tech Sheet 1657



Extra Light Duty

0350

To Suit Tube O.D.mm

£

VSD4LLMMB	4	3.70
VSD6LLMMD	6	4.00
VSD8LLMMD	8	4.65

Light Duty

0350

To Suit Tube O.D.mm

£

VSD6L/SMMB	6	1.80
VSD8L/SMMB	8	2.00
VSD10L/SMMB	10	2.30
VSD12L/SMMB	12	2.75
VSD15LMMB	15	3.65
VSD18LMMB	18	3.90
VSD22LMMB	22	6.25
VSD28LMMB	28	10.25
VSD35LMMB	35	20.40
VSD42LMMB	42	31.50

Heavy Duty

0350

To Suit Tube O.D.mm

£

VSD14SMMB	14	6.40
VSD16SMMB	16	3.70
VSD20SMMB	20	5.45
VSD25SMMB	25	7.80
VSD30SMMB	30	13.55
VSD38SMMB	38	24.90

WALPro Nut & Profile Ring



Extra Light Duty

0350

OD mm

bar

£

SR-M 4 LL	4	100	1.10
SR-M 6 LL	6	100	1.15
SR-M 8 LL	8	100	1.15

Light Duty

0350

OD mm

bar

£

PR-M 6 L	6	500	1.10
PR-M 8 L	8	500	1.20
PR-M 10 L	10	500	1.30
PR-M 12 L	12	400	1.55
PR-M 15 L	15	400	2.00
PR-M 18 L	18	400	3.30
PR-M 22 L	22	250	4.50
PR-M 28 L	28	250	7.55
PR-M 35 L	35	250	10.00
PR-M 42 L	42	250	11.30

Heavy Duty

0350

OD mm

bar

£

PR-M 6 S	6	800	1.20
PR-M 8 S	8	800	1.30
PR-M 10 S	10	800	1.65
PR-M 12 S	12	630	1.80
PR-M 14 S	14	630	2.95
PR-M 16 S	16	420	3.60
PR-M 20 S	20	420	5.00
PR-M 25 S	25	420	8.65
PR-M 30 S	30	420	10.70
PR-M 38 S	38	420	15.45

The colour of the product may vary from that illustrated, due to Health and Safety legislation controlling the use of chromium plating. The plating will be silver rather than the traditional gold. Mixed stock may be supplied during the manufacturer's transitional period.

Blanking Ends

Suitable for swivel end connectors.

Tech Sheet 1658



Light Duty

0350

OD mm

bar

£

VSK6L	6	500	4.05
VSK8L	8	500	4.70
VSK10L	10	500	5.60
VSK12L	12	400	6.55
VSK15L	15	400	9.15
VSK18L	18	400	13.45
VSK22L	22	250	19.15
VSK28L	28	250	35.60
VSK35L	35	250	54.70
VSK42L	42	250	79.30

Heavy Duty

0350

OD mm

bar

£

VSK6S	6	800	4.85
VSK8S	8	800	5.80
VSK10S	10	800	6.60
VSK12S	12	630	7.75
VSK14S	14	630	14.30
VSK16S	16	630	14.30
VSK20S	20	420	21.60
VSK25S	25	420	36.05
VSK30S	30	420	55.05
VSK38S	38	420	80.20