



Aluminium Ring Main System

Page Tech Sheet 10164

Working Temperature:
-20°C to +70°C

Maximum Working Pressure:
13 bar

N.B: Fittings 67, 84, 100, 150 & 200 will require 'Lugged Tube'

Equal 90° Elbow Connectors



Aluminium
20mm-200mm

0368	OD mm	Type	£
2009 1003 00	20	A	7.45
2009 2003 00	25	A	10.85
2009 4003 00	40	A	32.60
2009 5003 00	50	A	45.00
2009 6003 00	63	A	52.80
2014 6003 00	67	B	24.30
2009 7003 00	80	A	71.45
2014 7003 00	84	B	28.40
2009 8003 00	100	B	31.05
2009 9003 00	150	B	77.70
2009 A003 00	200	B	101.65

Equal 45° Elbow Connectors



Aluminium
20mm-50mm

0368	OD mm	Type	£
2009 1004 00	20	A	8.05
2009 2004 00	25	A	11.50
2009 4004 00	40	A	34.15
2009 5004 00	50	A	46.90

Equal Tee Connectors



Aluminium
20mm-200mm

0368	OD mm	Type	£
2009 1005 00	20	A	8.05
2009 2005 00	25	A	12.10
2009 4005 00	40	A	35.70
2009 5005 00	50	A	49.70
2009 6005 00	63	A	57.45
2014 6005 00	67	B	32.40
2009 7005 00	80	A	80.75
2014 7005 00	84	B	38.80
2009 8005 00	100	B	40.40
2009 9005 00	150	B	83.90
2009 A005 00	200	B	107.85


Reducing Stem Tee Connectors



Aluminium 20mm-200mm

0368	OD mm	Type	OD mm	Type	£
2009 2107 00	25	A	20	A	10.85
2009 4207 00	40	A	25	A	28.00
2009 5407 00	50	A	40	A	49.70
2009 6407 00	63	A	40	A	141.40
2009 6507 00	63	A	50	A	134.50
2014 6407 00	67	B	40	A	76.85
2014 6507 00	67	B	50	A	68.75
2009 7407 00	80	A	40	A	141.40
2009 7507 00	80	A	50	A	165.60
2009 7607 00	80	A	63	A	153.50
2014 7407 00	84	B	40	A	80.85
2014 7507 00	84	B	50	A	80.85
2014 7607 00	84	B	67	B	56.60
2009 8407 00	100	B	40	A	113.40
2009 8507 00	100	B	50	A	137.65
2009 8607 00	100	B	63	A	125.50
2014 8607 00	100	B	67	B	101.20
2009 8707 00	100	B	80	A	135.45
2014 8707 00	100	B	84	B	101.20
2009 9407 00	150	B	40	A	124.30
2009 9507 00	150	B	50	A	155.40
2014 9607 00	150	B	67	B	106.80
2009 9707 00	150	B	80	A	124.30
2014 9707 00	150	B	84	B	110.00
2009 9807 00	150	B	100	B	87.00
2009 A407 00	200	B	40	A	154.10
2009 A507 00	200	B	50	A	169.45
2009 A607 00	200	A	63	A	147.90
2009 A707 00	200	B	80	A	129.40
2009 A807 00	200	B	100	B	107.85
2009 A907 00	200	B	150	B	107.85

Female Straight Connectors



Aluminium
20mm-67mm, BSPP

0368	OD mm	Type	£	
2009 1119 00	20	A	3/4"	10.25
2009 2219 00	25	A	1"	15.55
2009 4419 00	40	A	1.1/2"	24.85
2009 5519 00	50	A	2"	34.15
2009 6619 00	63	A	2.1/2"	40.40
2014 6619 00	67	B	2.1/2"	52.55

Male Straight Connectors



Aluminium
20mm-84mm, BSPT

0368	OD mm	Type	£	
2009 1017 00	20	A	1/2"	9.30
2009 1117 00	20	A	3/4"	9.30
2009 2117 00	25	A	3/4"	14.00
2009 2217 00	25	A	1"	14.00
2009 4217 00	40	A	1"	24.85
2009 4317 00	40	A	1.1/4"	24.85
2009 4417 00	40	A	1.1/2"	24.85
2009 5417 00	50	A	1.1/2"	37.30
2009 5517 00	50	A	2"	37.30
2009 6517 00	63	A	2"	40.40
2009 6617 00	63	A	2.1/2"	40.40
2014 6517 00	67	B	2"	30.30
2014 6617 00	67	B	2.1/2"	30.30
2009 7617 00	80	A	2.1/2"	55.90
2009 7717 00	80	A	3"	55.90
2014 7617 00	84	B	2.1/2"	32.30
2014 7717 00	84	B	3"	32.30

End Cap



Aluminium 20mm-200mm

0368	OD mm	Type	£
2009 1006 00	20	A	6.50
2009 2006 00	25	A	9.60
2009 4006 00	40	A	9.70
2009 5006 00	50	A	19.40
2009 6006 00	63	A	29.10
2014 6006 00	67	B	32.40
2009 7006 00	80	A	62.15
2014 7006 00	84	B	42.15
2009 8006 00	100	B	45.00
2009 9006 00	150	B	58.25
2009 A006 00	200	B	77.00

Type A = Push-in Type
Type B = Lugged Type

Sizes 100, 150 & 200mm will not be available from stock in the UK. Standard delivery on these lines will be 4-6 weeks.