



# Plastic Plumbing Push-in Fittings



## Couplings



Straight

1400	OD mm	£
PEM0410W	10	3.05
PKM0415W	15	2.20
PKM0422W	22	3.40
PEM0428W	28	9.15



Reducing

1400	OD mm	OD mm	£
PKM201510W	15	10	5.10
PKM202215W	22	15	6.10



Brass BSPP Male

1400	OD mm	Thread	£
15MC	15	1/2"	8.35
22MC	22	3/4"	14.30



BSPP Female to Tap Connector

1400	OD mm	Thread	£
PEM3210W	10	1/2"	4.10
PEM3201W	15	1/2"	2.50
PEM3203W	15	3/4"	5.20
PEM3202W	22	3/4"	3.70

## Elbows



Equal

1400	OD mm	£
PEM0310W	10	3.85
PKM0315W	15	2.55
PKM0322W	22	4.10
PEM0328W	28	10.15

- Provides a swivel type connection.



Stem

1400	OD mm	Stem OD mm	£
PEM221010W	10	10	4.00
PKM221515W	15	15	4.85
PKM222222W	22	22	8.15



Brass Wing Back, BSPP Female

1400	OD mm	Thread	£
15WB	15	1/2"	15.10

- Suitable for normal hot and cold water services.
- Central heating applications, including pressurised and combi systems.
- Suitable for use with copper tube, use pipe inserts when using plastic tube.
- Manufactured to BS7291 Parts 1 & 3 Class S.
- Not to be used for gas, fuel oil or compressed air applications.

<b>Central Heating</b>	3 bar at 92°C
<b>Hot Water</b>	6 bar at 65°C
<b>Cold Water</b>	2 bar at 20°C

## Tees



Equal

1400	OD mm	£
PEM0210W	10	4.20
PKM0215W	15	3.75
PKM0222W	22	5.50
PEM0228W	28	14.45



Reducing

1400	OD A mm	OD B mm	OD C mm	£
PKM3022CW	15	15	22	6.30
PEM3022BW	22	15	15	6.65
PKM3022AW	22	22	15	6.30
PKM3022DW	22	15	22	8.85
PEM3028AW	28	28	22	16.75
PEM3028DW	28	22	28	16.75

## End Stops



1400	OD mm	£
PSE4610W	10	3.00
PKM4615W	15	2.90
PKM4622W	22	3.55

## Pipe Inserts

To be used on installation when using plastic pipe.



1400	ID mm	£
TSM10N	10	0.50
TSM15N	15	0.45
TSM22N	22	0.55
TSM28N	28	0.90