



Plastic Plumbing Push-in Fittings



Section 8 – Ring Main Systems

Reducers



1400			£
PEM061510W	10	15	2.65
PEM062215W	15	22	3.40
PEM062815W	15	28	7.10
PEM062822W	22	28	7.80

Connectors



Tap, BSPP Female

1400			£
PKMSTC1514	15	1/2" Straight	4.25
PKMSTC1516	15	3/4" Straight	5.05
PKMSTC2216	22	3/4" Straight	5.60

Maximum wall thickness of tank = 4mm.
Note: Requires hand tightening only



Tank

1400		£
CM0715S	15	3.90
CM0722S	22	4.95
CM0728S	28	19.10

Brass Drain Cock



1400		£
15BDC	15	10.55

Speedfit Drain Cocks cannot be used where collet covers are fitted. They can be used with a standard fitting fitted with a collet clip.

Service Valves

N.B: Hot and Cold water only 65°C max.
Not suitable for central heating systems.



1400		£
15ISV	15	8.95

Brass Chrome Plated



1400		£
10HSV	10	15.75
15HSV	15	18.90
22HSV	22	40.40

Brass Chrome Plated with Tap Connector BSPP Female



1400			£
15PTS	15	1/2"	18.75
22PTS	22	3/4"	45.95

Brass Chrome Plated Ball Valves

Suitable for central heating systems, each valve has a red and blue indice.



1400		£
10BV	10	22.15
15BV	15	24.20
22BV	22	48.45

Valves

N.B. Hot and cold water only 65°C max.



1400		£
15STV	15	11.10
22STV	22	16.90

Brass Stop



1400		£
15BSC	15	24.65

N.B. Hot and cold water only 65°C max.
Not suitable for central heating systems.



1400		£
15DCV	15	15.65

Taps



1400		£
15ESOT	15	8.00

N.B. Hot and cold water only 65°C max.



1400			£
15APT-B	15	3/4"	7.50