



# One Touch Plastic Push-in Fittings



**Temperature Range:**  
Brass: 0°C to +60°C  
Acetal: 0°C to +60°C

**Working Pressure:**  
10 bar (150 psi)

**Media:** Air & vacuum only.  
**Negative Pressure:** -750mm Hg (10Torr)

## Tube x Stem Connectors

Straights,  
Tube x Stem



1060	OD mm	Stem OD mm	1-99 £	100+ £
2028-8437	4	6	4.00	3.80
2028-8445	4	8	4.90	4.65
2028-8452	6	8	4.85	4.60
2028-8460	6	10	8.00	7.55
2028-8478	8	10	8.10	7.65
2028-8486	8	12	8.90	8.45
2028-8494	10	12	8.85	8.40

## Equal Double Joint Adaptor



Tube x Tube

1060	OD mm	1-99 £	100+ £
2028-8502	4	5.45	5.20
2028-8510	6	6.10	5.75
2028-8528	8	6.90	6.55
2028-8536	10	7.50	7.15
2028-8544	12	9.60	9.15

## Tube Plug



Tube

1060	OD mm	1-99 £	100+ £
2033-8505	4	6.30	5.95
2033-8513	6	6.90	6.55
2033-8521	8	7.50	7.15
2033-8539	10	9.20	8.75
2033-8547	12	10.05	9.50

Elbows,  
Tube x Stem



1060	OD mm	Stem OD mm	1-99 £	100+ £
2024-2566	4	4	4.40	4.20
2024-2574	6	6	4.75	4.50
2024-2582	8	8	5.85	5.55
2024-2590	10	10	8.65	8.25
2024-2608	12	12	10.60	10.10

## Reducer



Tube x Tube

1060	Stem OD mm	Stem OD mm	1-99 £	100+ £
2028-8551	6	4	6.90	6.55
2028-8569	8	4	7.50	7.15
2028-8577	8	6	7.50	7.15
2028-8585	10	6	7.70	7.30
2028-8593	10	8	7.70	7.30
2028-8601	12	8	8.80	8.35
2028-8619	12	10	8.80	8.35

## Manual Shut-off Valves

**Working Pressure:**  
7 bar  
(100 psi)



Tube x Tube, Venting

1060	OD mm	OD mm	£
HVFF06-06	6	6	18.00
HVFF08-06	8	6	18.00
HVFF08-08	8	8	16.85
HVFF10-10	10	10	18.55
HVFF12-10	12	10	18.55
HVFF12-12	12	12	18.55

Ys,  
Tube x Stem



1060	OD mm	Stem OD mm	1-99 £	100+ £
2024-2616	4	4	5.40	5.15
2024-2624	6	6	6.70	6.40
2024-2632	8	8	8.25	7.80
2024-2640	10	10	10.75	10.20
2024-2657	12	12	12.75	12.15

## Plug



Tube

1060	OD mm	1-99 £	100+ £
2028-8627	4	1.00	0.95
2028-8635	6	1.30	1.25
2028-8643	8	1.35	1.30
2028-8668	10	1.55	1.45
2028-8684	12	1.90	1.80

## Manual Flow Controller, Uni-directional



Straight, Tube x Tube

1060	OD mm	£
2022-9720	4	14.05
2022-9746	6	16.15
2022-9753	8	17.00
2022-9761	10	23.30
2022-9779	12	26.25