



One Touch NPT Plastic Push-in Fittings, Metric



Temperature Range:
Brass: 0°C to +60°C
Acetal: 0°C to +60°C

Working Pressure:
10 bar (150 psi)

Media: Air & vacuum only. **Negative Pressure:** -750mm Hg (10Torr)

Male Run Leg, Swivel Tees



Male Thread, NPT

1060	OD mm	£
2111-3485	4	1/8" 3.45
2111-3519	4	1/4" 3.80
2111-3527	6	1/8" 5.65
2111-3535	6	1/4" 5.45
2111-3550	6	3/8" 5.75
2111-3568	8	1/8" 4.85
2111-3576	8	1/4" 5.25
2111-3584	8	3/8" 5.75
2111-3592	8	1/2" 8.30
2111-3600	10	1/4" 5.75
2111-3618	10	3/8" 6.20
2111-3626	10	1/2" 6.80
2111-3634	12	1/4" 6.20
2111-3642	12	3/8" 6.80
2111-3659	12	1/2" 7.20

Male Stud Swivel Ys



Male Thread, NPT

1060	OD mm	£
2111-3667	4	1/8" 3.45
2111-3675	6	1/8" 3.80
2111-3683	6	1/4" 4.30
2111-3691	6	3/8" 4.65
2111-3709	8	1/8" 4.30
2111-3717	8	1/4" 5.60
2111-3725	8	3/8" 4.85
2111-3733	8	1/2" 6.20
2111-3758	10	1/4" 4.85
2111-3766	10	3/8" 5.15
2111-3774	10	1/2" 6.80
2111-3782	12	1/4" 6.20
2111-3790	12	3/8" 7.90
2111-3808	12	1/2" 8.65

Female Bulkhead Connectors



Female Thread, NPT

1060	OD mm	£
2111-3816	4	1/8" 5.10
2111-3832	4	1/4" 4.25
2111-3840	6	1/8" 5.95
2111-3857	6	1/4" 7.00
2111-3865	6	3/8" 6.20
2111-3873	6	1/2" 9.10
2111-3881	8	1/8" 5.95
2111-3899	8	1/4" 7.00
2111-3907	8	3/8" 6.20
2111-3915	8	1/2" 9.10
2111-3923	10	1/4" 6.20
2111-3931	10	3/8" 8.30
2111-3949	10	1/2" 7.45
2111-3956	12	1/4" 7.25
2111-3964	12	3/8" 7.45
2111-3972	12	1/2" 10.30

Banjos



Male Thread, NPT

1060	OD mm	£
2111-4020	4	1/8" 3.80
2111-4038	6	1/8" 6.00
2111-4053	6	1/4" 6.70
2111-4061	8	1/8" 4.85
2111-4079	8	1/4" 6.70
2111-4087	8	3/8" 5.75
2111-4095	10	3/8" 6.20
2111-4103	10	1/2" 6.80
2111-4111	12	1/4" 6.45
2111-4129	12	3/8" 8.65
2111-4137	12	1/2" 7.20

Female Thread, NPT

1060	OD mm	£
2111-4145	4	1/8" 4.80
2111-4152	4	1/4" 4.85
2111-4160	6	1/8" 5.75
2111-4178	6	1/4" 6.60
2111-4186	6	3/8" 7.35
2111-4202	8	1/4" 6.60
2111-4210	8	3/8" 7.25
2111-4228	8	1/2" 8.75
2111-4236	10	1/4" 7.25
2111-4244	10	3/8" 7.80
2111-4251	10	1/2" 8.50
2111-4269	12	1/4" 7.80
2111-4277	12	3/8" 8.25
2111-4285	12	1/2" 8.55

Reducing Manifolds



Male Thread, NPT, 3 Outlets

1060	OD mm	OD mm	£
2111-3980	6	4	1/8" 6.75
2111-3998	8	4	1/4" 6.75
2111-4004	8	6	1/4" 9.00
2111-4012	10	8	3/8" 9.35

Manual Flow Control Elbows



Male Thread, NPT

1060	OD mm	£
2111-4293	4	1/8" 12.25
2111-4301	4	1/4" 12.25
2111-4319	6	1/8" 13.25
2111-4327	6	1/4" 13.25
2111-4335	6	3/8" 16.95
2111-4343	8	1/8" 13.25
2111-4350	8	1/4" 13.25
2111-4368	8	3/8" 16.95
2111-4376	8	1/2" 15.85
2111-4384	10	1/4" 12.25
2111-4392	10	3/8" 16.95
2111-4400	10	1/2" 15.85
2111-4418	12	1/4" 12.90
2111-4426	12	3/8" 15.20
2111-4434	12	1/2" 17.15

Manual Flow Control Valves



Male Thread, NPT x Tube

1060	OD mm	£
2111-4442	6	1/8" 17.40
2111-4459	6	1/4" 20.70
2111-4467	6	3/8" 21.85
2111-4475	8	1/8" 21.80
2111-4483	8	1/4" 20.70
2111-4491	8	3/8" 21.85

- Hydraulics
- Hydraulic QRC
- Pneumatic QRC
- Ind. Air Prep., Monitor & Test
- KELM™ Pneumatics
- Pneumatic & Vacuum Equipment
- Valves
- Ring Main Systems
- Adaptors & Fittings
- Stainless Steel
- Malleable Iron
- Hose, Tubing & Couplings
- Clamps & Clips
- Sprays & Adhesives
- Blow Guns & Vacuum
- Wash Down & Fuelling
- Air Tools
- Tools, Hardware & PPE