



One Touch+ Plastic Push-in Fittings (16 bar Rated)



Page Tech Sheet 10019



Working Temperature:
-0°C to +60°C



Maximum Working Pressure:
16 bar (220 psi)

Media:
Air & vacuum only.

Negative Pressure:
-750mm Hg (10Torr)



Male Studs



Male Thread, Metric & BSPT

1060	OD mm	Thread	£
2175-0849	4	M5	2.35
2175-0850	4	M6	2.35
2175-0851	4	1/8"	2.35
2175-0852	4	1/4"	2.35
2175-0853	4	3/8"	2.35
2175-0854	6	M5	2.35
2175-0855	6	M6	2.35
2175-0856	6	1/8"	2.35
2175-0857	6	1/4"	2.35
2175-0858	6	3/8"	3.45
2175-0859	6	1/2"	4.50
2175-0860	8	1/8"	2.35
2175-0861	8	1/4"	2.35
2175-0862	8	3/8"	3.45
2175-0863	8	1/2"	4.50
2175-0864	10	1/8"	3.55
2175-0865	10	1/4"	3.55
2175-0866	10	3/8"	4.75
2175-0867	10	1/2"	4.75
2175-0868	12	1/4"	4.75
2175-0869	12	3/8"	4.75
2175-0870	12	1/2"	4.75
2207-0684	14	3/8"	10.20
2207-0685	14	1/2"	10.20
2207-0686	16	3/8"	10.20
2207-0687	16	1/2"	10.20

Female Studs



Female Thread, BSPP

1060	OD mm	Thread	£
2175-0887	4	1/8"	2.80
2175-0888	4	1/4"	2.80
2175-0889	6	1/8"	2.80
2175-0890	6	1/4"	3.45
2175-0891	6	3/8"	4.00
2175-0892	8	1/8"	3.45
2175-0893	8	1/4"	3.45
2175-0894	8	3/8"	4.00
2175-0895	8	1/2"	6.55
2175-0896	10	1/8"	4.30
2175-0897	10	1/4"	4.30
2175-0898	10	3/8"	4.30
2175-0899	10	1/2"	6.65
2175-0900	12	1/4"	6.65
2175-0901	12	3/8"	6.65
2175-0902	12	1/2"	6.65
2207-0692	14	3/8"	13.90
2207-0693	14	1/2"	13.90
2207-0694	16	3/8"	13.90
2207-0695	16	1/2"	13.90

Male Thread, BSPP

1060	OD mm	Thread	£
2175-0924	4	1/8"	4.15
2175-0925	4	1/4"	4.25
2175-0926	6	1/8"	4.15
2175-0927	6	1/4"	4.30
2175-0928	6	3/8"	4.95
2175-0929	8	1/8"	4.75
2175-0930	8	1/4"	4.95
2175-0931	8	3/8"	5.25
2175-0932	8	1/2"	7.55
2175-0933	10	1/8"	6.65
2175-0934	10	1/4"	6.55
2175-0935	10	3/8"	6.65
2175-0936	10	1/2"	7.80
2175-0937	12	1/4"	7.80
2175-0938	12	3/8"	8.10
2175-0939	12	1/2"	8.55
2207-0700	14	3/8"	20.45
2207-0701	14	1/2"	20.45
2207-0702	16	3/8"	20.45
2207-0703	16	1/2"	20.45

Male Stud Swivel Elbows



Male Thread, Metric & BSPT

1060	OD mm	Thread	£
2175-0903	4	M5	3.45
2175-0904	4	M6	3.45
2175-0905	4	1/8"	3.45
2175-0906	4	1/4"	3.45
2175-0907	6	M5	3.45
2175-0908	6	M6	3.45
2175-0909	6	1/8"	3.45
2175-0910	6	1/4"	3.45
2175-0911	6	3/8"	4.00
2175-0912	6	1/2"	6.55
2175-0913	8	1/8"	3.80
2175-0914	8	1/4"	3.80
2175-0915	8	3/8"	4.20
2175-0916	8	1/2"	6.55
2175-0917	10	1/8"	4.20
2175-0918	10	1/4"	4.20
2175-0919	10	3/8"	4.50
2175-0920	10	1/2"	7.55
2175-0921	12	1/4"	7.55
2175-0922	12	3/8"	7.55
2175-0923	12	1/2"	7.55
2207-0696	14	3/8"	20.45
2207-0697	14	1/2"	20.45
2207-0698	16	3/8"	20.45
2207-0699	16	1/2"	20.45

Extended Male Thread, Metric & BSPT

1060	OD mm	Thread	£
2175-0940	4	M5	3.50
2175-0941	4	1/8"	4.40
2175-0942	4	1/4"	4.40
2175-0943	6	M5	4.40
2175-0944	6	1/8"	3.25
2175-0945	6	1/4"	4.40
2175-0946	6	3/8"	4.40
2175-0947	8	1/8"	3.50
2175-0948	8	1/4"	4.70
2175-0949	8	3/8"	4.90
2175-0950	10	1/8"	4.90
2175-0951	10	1/4"	6.65
2175-0952	10	3/8"	6.65
2175-0953	10	1/2"	7.25
2175-0954	12	1/4"	7.25
2175-0955	12	3/8"	9.80
2175-0956	12	1/2"	9.80

Male Thread, BSPP



1060	OD mm	Thread	£
2175-0871	4	1/8"	2.60
2175-0872	4	1/4"	2.70
2175-0873	6	1/8"	2.60
2175-0874	6	1/4"	2.70
2175-0875	6	3/8"	3.55
2175-0876	8	1/8"	3.10
2175-0877	8	1/4"	3.10
2175-0878	8	3/8"	3.70
2175-0879	8	1/2"	5.25
2175-0880	10	1/8"	3.80
2175-0881	10	1/4"	4.10
2175-0882	10	3/8"	3.80
2175-0883	10	1/2"	4.50
2175-0884	12	1/4"	4.70
2175-0885	12	3/8"	4.70
2175-0886	12	1/2"	5.35
2207-0688	14	3/8"	11.20
2207-0689	14	1/2"	11.20
2207-0690	16	3/8"	11.20
2207-0691	16	1/2"	11.20

Extended Male Thread, BSPP

1060	OD mm	Thread	£
2175-0957	4	1/8"	3.50
2175-0958	4	1/4"	3.70
2175-0959	6	1/8"	3.90
2175-0960	6	1/4"	4.00
2175-0961	6	3/8"	4.80
2175-0962	8	1/8"	4.30
2175-0963	8	1/4"	4.25
2175-0964	10	1/8"	5.25
2175-0965	10	1/4"	5.35
2175-0966	10	3/8"	5.75
2175-0967	12	3/8"	7.55