



One Touch+ Plastic Push-in Fittings (16 bar Rated)



Page Tech Sheet 10019



Working Temperature:
-0°C to +60°C



Maximum Working Pressure:
16 bar (220 psi)

Media:
Air & vacuum only.

Negative Pressure:
-750mm Hg (10Torr)

Section 9 – Adaptors & Fittings

Tube x Tube Connectors



Equal Ys

1060	OD mm	£
2175-1042	4	4.20
2175-1043	6	4.20
2175-1044	8	4.20
2175-1045	10	5.25
2175-1046	12	6.55
2207-0710	14	8.90
2207-0711	16	8.90

Tube x Stem Connectors



Straights, Tube x Stem

1060	OD mm	Stem OD mm	£
2175-1061	4	6	2.35
2175-1062	4	8	2.80
2175-1063	6	8	3.00
2175-1064	6	10	4.75
2175-1065	8	10	4.80
2175-1066	10	12	3.35

Single Banjos



Male Thread, Metric & BSPT

1060	OD mm	Thread	£
2175-1080	4	M5	12.70
2175-1081	4	M6	12.70
2175-1082	4	1/8"	12.70
2175-1083	6	M5	12.70
2175-1084	6	M6	12.70
2175-1085	6	1/8"	13.70
2175-1086	6	1/4"	13.70
2175-1087	6	3/8"	13.80
2175-1088	8	1/8"	13.70
2175-1089	8	1/4"	13.70
2175-1090	8	3/8"	17.60
2175-1091	10	1/4"	15.00
2175-1092	10	3/8"	17.60
2175-1093	10	1/2"	20.80
2175-1094	12	1/4"	20.00
2175-1095	12	3/8"	20.00
2175-1096	12	1/2"	20.85

Hydraulics

Hydraulic QRC

Pneumatic QRC

Ind. Air Prep., Monitor & Test

KELM™ Pneumatics

Pneumatic & Vacuum Equipment

Valves

Ring Main Systems

Adaptors & Fittings

Unequal Ys



1060	OD mm	OD mm	£
2175-1047	4	6	5.35
2175-1048	6	8	5.35
2175-1049	8	10	6.55
2175-1050	10	12	6.00

Elbows, Tube x Stem



1060	OD mm	Stem OD mm	£
2175-1067	4	4	9.60
2175-1068	6	6	10.55
2175-1069	8	8	11.95
2175-1070	10	10	13.10
2175-1071	12	12	17.20

Plugs



Tube

1060	OD mm	£
2175-1075	4	1.10
2175-1076	6	1.30
2175-1077	8	1.45
2175-1078	10	1.65
2175-1079	12	2.05

Equal Crosses



1060	OD mm	£
2175-1051	4	7.25
2175-1052	6	7.40
2175-1053	8	8.45
2175-1054	10	9.60
2175-1055	12	10.80

Ys, Tube x Stem



1060	OD mm	Stem OD mm	£
2175-1072	6	6	8.55
2175-1073	8	8	9.50
2175-1074	10	10	10.10

Equal Bulkheads



1060	OD mm	£
2175-1056	4	5.80
2175-1057	6	5.80
2175-1058	8	7.25
2175-1059	10	8.75
2175-1060	12	10.45