



Micro One Touch NPT & UNF Plastic Push-in Fittings



Working Temperature:
-0°C to +60°C

Maximum Working Pressure:
10 bar (150 psi)

40% less volume & a 20% smaller OD than the standard One Touch Design

Micro One Touch fittings are specially designed for pneumatic systems that are use in confined spaces, saving you time & money on installations.

Male Tees



Male Thread, Branch, NPT

0315	OD	1-9	10+
PT1/8-N00C	1/8" 1/16"	6.20	4.95
PT5/32-N00C	5/32" 1/16"	6.20	4.95
PT1/4-N00C	1/4" 1/16"	6.20	4.95
PT1/8-N01C	1/8" 1/8"	6.20	4.95
PT5/32-N01C	5/32" 1/8"	6.20	4.95
PT1/4-N01C	1/4" 1/8"	6.20	4.95

Male Thread, Branch, UNF

0315	OD	1-9	10+
PT1/8-U10C	1/8" 10-32	6.20	4.95
PT5/32-U10C	5/32" 10-32	6.20	4.95
PT1/4-U10C	1/4" 10-32	6.20	4.95



Male Thread, Run, NPT

0315	OD	1-9	10+
PST1/8-N00C	1/8" 1/16"	6.20	4.95
PST5/32-N00C	5/32" 1/16"	6.20	4.95
PST1/4-N00C	1/4" 1/16"	6.20	4.95
PST1/8-N01C	1/8" 1/8"	6.20	4.95
PST5/32-N01C	5/32" 1/8"	6.20	4.95
PST1/4-N01C	1/4" 1/8"	6.20	4.95

Male Thread, Run, UNF

0315	OD	1-9	10+
PST1/8-U10C	1/8" 10-32	6.20	4.95
PST5/32-U10C	5/32" 10-32	6.20	4.95
PST1/4-U10C	1/4" 10-32	6.20	4.95

Equal Connectors



Straights

0315	OD	1-9	10+
PUC1/8C	1/8"	3.55	2.80
PUC5/32C	5/32"	3.55	2.80
PUC1/4C	1/4"	3.55	2.80



Elbows

0315	OD	1-9	10+
PUL1/8C	1/8"	3.55	2.80
PUL5/32C	5/32"	3.55	2.80
PUL1/4C	1/4"	3.55	2.80



Tees

0315	OD	1-9	10+
PUT1/8C	1/8"	4.95	3.95
PUT5/32C	5/32"	4.95	3.95
PUT1/4C	1/4"	4.95	3.95



Ys

0315	OD	1-9	10+
PY5/32C	5/32"	4.80	3.85
PY1/4C	1/4"	4.80	3.85

Customers who bought from this page also purchased **KELM™ Specialist Valves** – see pages 517-518



Hydraulics

Hydraulic QRC

Pneumatic QRC

Ind. Air Prep, Monitor & Test

KELM™ Pneumatics

Pneumatic & Vacuum Equipment

Valves

Ring Main Systems

Adaptors & Fittings

Stainless Steel

Malleable Iron

Hose, Tubing & Couplings

Clamps & Clips

Sprays & Adhesives

Blow Guns & Vacuum

Wash Down & Fuelling

Air Tools

Tools, Hardware & PPE