



# DIN 2353 Body Only Fittings



## Straight Coupling



Light Duty

0350	OD mm	£
GS 6 L	6	2.00
GS 8 L	8	2.15
GS 10 L	10	2.80
GS 12 L	12	3.30
GS 15 L	15	4.80
GS 18 L	18	6.70
GS 22 L	22	9.30
GS 28 L	28	18.10
GS 35 L	35	25.15
GS 42 L	42	35.55

Heavy Duty

0350	OD mm	£
GS 6 S	6	2.75
GS 8 S	8	3.00
GS 10 S	10	3.60
GS 12 S	12	4.15
GS 14 S	14	8.45
GS 16 S	16	7.45
GS 20 S	20	11.45
GS 25 S	25	18.85
GS 30 S	30	29.00
GS 38 S	38	37.55

## Straight Bulkhead Coupling



Light Duty

0350	OD mm	£
GSS 6 L	6	6.10
GSS 8 L	8	6.05
GSS 10 L	10	7.90
GSS 12 L	12	8.85
GSS 15 L	15	14.10
GSS 18 L	18	22.25
GSS 22 L	22	27.95
GSS 28 L	28	41.25
GSS 35 L	35	66.40
GSS 42 L	42	93.35

Heavy Duty

0350	OD mm	£
GSS 6 S	6	7.85
GSS 8 S	8	9.10
GSS 10 S	10	10.35
GSS 12 S	12	14.40
GSS 14 S	14	23.80
GSS 16 S	16	22.05
GSS 20 S	20	35.00
GSS 25 S	25	54.80
GSS 30 S	30	66.75
GSS 38 S	38	112.10

## Equal Elbow



Light Duty

0350	OD mm	£
WS 6 L	6	7.45
WS 8 L	8	7.90
WS 10 L	10	8.40
WS 12 L	12	9.80
WS 15 L	15	13.35
WS 18 L	18	16.80
WS 22 L	22	24.15
WS 28 L	28	37.25
WS 35 L	35	55.80
WS 42 L	42	78.35

Heavy Duty

0350	OD mm	£
WS 6 S	6	8.60
WS 8 S	8	9.05
WS 10 S	10	10.35
WS 12 S	12	11.80
WS 14 S	14	20.10
WS 16 S	16	17.20
WS 20 S	20	23.55
WS 25 S	25	38.20
WS 30 S	30	55.80
WS 38 S	38	80.00

## Equal Tee



Light Duty

0350	OD mm	£
TS 6 L	6	8.45
TS 8 L	8	8.10
TS 10 L	10	9.00
TS 12 L	12	12.90
TS 15 L	15	12.00
TS 18 L	18	15.70
TS 22 L	22	21.80
TS 28 L	28	31.50
TS 35 L	35	49.90
TS 42 L	42	80.80

Heavy Duty

0350	OD mm	£
TS 6 S	6	9.80
TS 8 S	8	10.90
TS 10 S	10	11.80
TS 12 S	12	12.00
TS 14 S	14	16.40
TS 16 S	16	15.80
TS 20 S	20	23.00
TS 25 S	25	31.80
TS 30 S	30	48.85
TS 38 S	38	77.30

## WALFORM

The WALFORM cold reshaping machine creates a profile ring in the tube itself resulting in the recognized pressure point felt during in service assembly.

