

Brass Push-in Plumbing Tube Fittings



ITAP-FIT® Fitting

Suitable for:
Copper, PEX & Polybutylene Pipe.

Working Temperature:
-20°C to +120°C



Maximum Working Pressure:
Copper Pipe: 20 bar @ 25°C, 10 bar @ 90°C
PEX & Polybutylene Pipe: 12 bar @ 25°C, 5 bar @ 90°C



Female Stud Coupling

0089	OD mm		£
610B038012	12	3/8"	5.35
610B012012	12	1/2"	6.10
610B012014	14	1/2"	6.20
610B012015	15	1/2"	6.45
610B012016	16	1/2"	6.50
610B012018	18	1/2"	8.25
610B012020	20	1/2"	8.70
610B034018	18	3/4"	8.55
610B034022	22	3/4"	9.50
610B034025	25	3/4"	11.40
610B100028	28	1"	14.20



Male Stud Coupling

0089	OD mm		£
615B038012	12	3/8"	4.20
615B038014	14	3/8"	4.95
615B012012	12	1/2"	4.85
615B012014	14	1/2"	5.00
615B012015	15	1/2"	5.10
615B012016	16	1/2"	5.10
615B012018	18	1/2"	7.15
615B012020	20	1/2"	7.50
615B034018	18	3/4"	7.40
615B034022	22	3/4"	8.65
615B034025	25	3/4"	10.85
615B100028	28	1"	14.00



Female Stud 90° Elbow, BSPT

0089	OD mm		£
645B038012	12	3/8"	5.80
645B012012	12	1/2"	6.60
645B012014	14	1/2"	7.15
645B012015	15	1/2"	7.40
645B012016	16	1/2"	8.00
645B012018	18	1/2"	9.90
645B012020	20	1/2"	10.30
645B034018	18	3/4"	11.20
645B034022	22	3/4"	12.45
645B034025	25	3/4"	14.10
645B100028	28	1"	19.00



Female Stud 90° Elbow (Wall Mount), BSPT

0089	OD mm		£
648B038012	12	3/8"	7.70
648B012012	12	1/2"	8.35
648B012014	14	1/2"	9.25
648B012015	15	1/2"	9.70
648B012016	16	1/2"	10.30
648B012018	18	1/2"	11.75
648B012020	20	1/2"	13.55
648B034018	18	3/4"	12.90
648B034022	22	3/4"	13.10



Male Stud 90° Elbow, BSPT

0089	OD mm		£
640B038012	12	3/8"	5.65
640B012012	12	1/2"	5.90
640B012014	14	1/2"	6.60
640B012015	15	1/2"	7.00
640B012016	16	1/2"	7.55
640B012018	18	1/2"	9.35
640B012020	20	1/2"	9.95
640B034018	18	3/4"	10.35
640B034022	22	3/4"	11.70
640B034025	25	3/4"	13.55
640B100028	28	1"	18.20



Female Branch Tee, BSPT

0089	OD mm		£
635B012012	12	1/2"	9.50
635B012014	14	1/2"	10.25
635B012015	15	1/2"	10.55
635B012016	16	1/2"	11.10
635B012018	18	1/2"	14.60
635B012020	20	1/2"	16.40
635B034018	18	3/4"	15.25
635B034022	22	3/4"	18.00
635B034025	25	3/4"	21.70
635B100028	28	1"	26.15



Disconnecting Clip

0089	OD mm	£
671012	12mm	0.75
671014	14mm	0.80
671015	15mm	0.80
671016	16mm	0.80
671018	18mm	0.80
671020	20mm	0.90
671022	22mm	0.90
671025	25mm	1.00
671028	28mm	1.00



Depth Gauge

0089	£
685012028	9.60