







Axial Valves




4202..20 Normally Closed Axial Valve with FKM Seal, Female BSPP Thread

	<p>Nickel-plated brass, FKM</p> 	C		F	G	H	H1	L	kg
		G3/8	4202 10 17 20	22	46	54	31	98	0.815
G1/2	4202 15 21 20	27	52	60	35	112	1.092		
G3/4	4202 20 27 20	33	64	70	38	135	1.624		
G1	4202 25 34 20	41	69	76	41.5	143	2.033		
G1¼	4202 32 42 20*	50	86	91	48	165	3.266		
G1½	4202 40 49 20*	60	96	102	54	180	4.195		
G2	4202 50 48 20*	75	109	115	60.5	207	6.465		
Pilot port: G1/8 - Delivered with a silencer *Models with CE marking									




4202..30 Normally Closed Axial Valve with EPDM Seal, Female BSPP Thread

	<p>Nickel-plated brass, EPDM</p> 	C		F	G	H	H1	L	kg
		G3/8	4202 10 17 30	22	46	54	31	98	0.828
G1/2	4202 15 21 30	27	52	60	35	112	1.098		
G3/4	4202 20 27 30	33	64	70	38	135	1.624		
G1	4202 25 34 30	41	69	76	41.5	143	1.998		
G1¼	4202 32 42 30*	50	86	91	48	165	3.315		
G1½	4202 40 49 30*	60	96	102	54	180	4.195		
G2	4202 50 48 30*	75	109	115	60.5	207	6.360		
Pilot port: G1/8 - Delivered with a silencer *Models with CE marking									




4212..20 Normally Open Axial Valve with FKM Seal, Female BSPP Thread

	<p>Nickel-plated brass, FKM</p> 	C		F	G	H	H1	L	kg
		G3/8	4212 10 17 20	22	46	54	31	98	0.829
G1/2	4212 15 21 20	27	52	60	35	112	1.100		
G3/4	4212 20 27 20	33	64	70	38	135	1.637		
G1	4212 25 34 20	41	69	76	41.5	143	2.037		
G1¼	4212 32 42 20*	50	86	91	48	165	0.030		
G1½	4212 40 49 20*	60	96	102	54	180	4.188		
G2	4212 50 48 20*	75	109	115	60.5	207	6.555		
Pilot port: G1/8 - Delivered with a silencer *Models with CE marking									

4212..30 Normally Open Axial Valve with EPDM seal, Female BSPP Thread

	<p>Nickel-plated brass, EPDM</p> 	C		F	G	H	H1	L	kg
		G3/8	4212 10 17 30	22	46	54	31	98	0.827
G1/2	4212 15 21 30	27	52	60	35	112	1.152		
G3/4	4212 20 27 30	33	64	70	38	135	1.575		
G1	4212 25 34 30	41	69	76	41.5	143	2.055		
G1¼	4212 32 42 30*	50	86	91	48	165	3.301		
G1½	4212 40 49 30*	60	96	102	54	180	4.775		
G2	4212 50 48 30*	75	109	115	60.5	207	6.360		
Pilot port: G1/8 - Delivered with a silencer *Models with CE marking									

4222..20 Double-Acting Axial Valve with FKM Seal, Female BSPP Thread

	<p>Nickel-plated brass, FKM</p> 	C		F	G	H	H1	L	kg
		G3/8	4222 10 17 20	22	46	54	31	98	0.802
G1/2	4222 15 21 20	27	52	60	35	112	1.063		
G3/4	4222 20 27 20	33	64	70	38	135	1.572		
G1	4222 25 34 20	41	69	76	41.5	143	1.942		
G1¼	4222 32 42 20*	50	86	91	48	165	3.058		
G1½	4222 40 49 20*	60	96	102	54	180	3.995		
G2	4222 50 48 20*	75	109	115	60.5	207	6.275		
Pilot port: G1/8 *Models with CE marking									