

Axial Valves

4222..30 Double Acting Axial Valve with EPDM seal, Female BSPP Thread

	<p>Nickel-plated brass, EPDM</p>	C		F	G	H	H1	L	kg
		G3/8	4222 10 17 30	22	46	54	31	98	0.832
G1/2	4222 15 21 30	27	52	60	35	112	1.046		
G3/4	4222 20 27 30	33	64	70	38	135	1.662		
G1	4222 25 34 30	41	69	76	41.5	143	1.938		
G1¼	4222 32 42 30*	50	86	91	48	165	3.301		
G1½	4222 40 49 30*	60	96	102	54	180	4.260		
G2	4222 50 48 30*	75	109	115	60.5	207	6.520		

Pilot port: G1/8
Delivered with a silencer
*Models with CE marking

4298 Sub-Base for Solenoid Pilot Valve

	<p>Treated aluminium, NBR</p>	C		kg
		M5x0.8	4298 00 01	0.095

The sub-base is fitted directly to the axial valve and allows the mounting of a 15x15 solenoid valve.
Supplied with 2 fixing bolts, silencer and seals.

4298 Mini-Solenoid Valve 1W/12VA

	<p>Anodised aluminium</p>	Voltage		kg
		24V $\overline{\text{---}}$ CC*	4298 01 01	0.052
24V \sim CA**	4298 01 02	0.058		
110V \sim CA**	4298 02 01	0.051		
220V \sim CA**	4298 02 02	0.054		

*Direct current
**Alternating current

4299 Pneumatic Button/Electro-Pneumatic

	<p>Nickel-plated brass</p>	Contact		kg
		Standard*	4299 01 01	0.085
With key*	4299 01 02	0.110		
Standard**	4299 02 01	0.102		
With key**	4299 02 02	0.124		

Bulkhead fixing hole diameter: Ø22 mm
*1 pneumatic contact
**1 electro-pneumatic contact
Available upon request only