


Miniature Regulators with External Adjustment

7660

Miniature Flow Regulator Exhaust, Male BSPP and Metric Thread



Technical polymer, nickel-plated brass, NBR




| ØD | C | | F | G | H min | H max | L | L1 | kg |
|----|--------|----------------------------|----|------|-------|-------|------|------|-------|
| 3 | M3x0.5 | 7660 03 09 | 6 | 9 | 23.5 | 26 | 17 | 4.5 | 0.007 |
| | M5x0.8 | 7660 03 19 | 6 | 9 | 23.5 | 26 | 17 | 4.5 | 0.006 |
| 4 | M3x0.5 | 7660 04 09 | 6 | 9 | 23.5 | 26 | 16.5 | 4.5 | 0.007 |
| | M5x0.8 | 7660 04 19 | 6 | 9 | 23.5 | 26 | 17 | 4.5 | 0.006 |
| 6 | G1/8 | 7660 06 10 | 7 | 11.5 | 27 | 29.5 | 18 | 6 | 0.012 |
| | M5x0.8 | 7660 06 19 | 6 | 9 | 23.5 | 26 | 18 | 4.5 | 0.007 |
| 8 | G1/4 | 7660 08 13 | 8 | 12 | 30 | 32.5 | 19 | 6 | 0.019 |
| | G1/8 | 7660 08 10 | 13 | 14 | 26.5 | 31 | 26 | 7 | 0.021 |
| | G3/8 | 7660 08 17 | 20 | 23 | 36 | 42 | 29 | 11.5 | 0.062 |

7665

Miniature Flow Regulator Exhaust, Male BSPT Thread



Technical polymer, nickel-plated brass, NBR



| ØD | C | | F | G | H min | H max | L | L1 | kg |
|----|------|----------------------------|----|------|-------|-------|------|-----|-------|
| 4 | R1/8 | 7665 04 10 | 7 | 11.5 | 25 | 27.5 | 18 | 6 | 0.012 |
| | R1/8 | 7665 06 10 | 7 | 11.5 | 25 | 27.5 | 18.5 | 6 | 0.012 |
| 6 | R1/4 | 7665 06 13 | 8 | 13.5 | 27.5 | 30 | 19 | 7 | 0.019 |
| | R3/8 | 7665 06 17 | 17 | 13.5 | 31.5 | 34 | 19 | 7 | 0.025 |
| 8 | R1/8 | 7665 08 10 | 13 | 14 | 24 | 28.5 | 26 | 7 | 0.021 |
| | R3/8 | 7665 08 17 | 16 | 19 | 25 | 29 | 27.5 | 9.5 | 0.033 |


Pre-coated thread

7669

Miniature Flow Regulator Supply, Male BSPP and Metric Thread



Technical polymer, nickel-plated brass, NBR




| ØD | C | | F | G | H min | H max | L | L1 | kg |
|----|--------|----------------------------|----|------|-------|-------|------|------|-------|
| 3 | M3x0.5 | 7669 03 09 | 6 | 9 | 23.5 | 26 | 17 | 4.5 | 0.008 |
| | M5x0.8 | 7669 03 19 | 6 | 9 | 23.5 | 26 | 17 | 4.5 | 0.007 |
| 4 | M5x0.8 | 7669 04 19 | 6 | 9 | 23.5 | 26 | 17 | 4.5 | 0.006 |
| | G1/8 | 7669 04 10 | 7 | 11.5 | 27 | 29.5 | 18 | 6 | 0.012 |
| 6 | M5x0.8 | 7669 06 19 | 6 | 9 | 23.5 | 26 | 18 | 4.5 | 0.007 |
| | G1/8 | 7669 06 10 | 7 | 11.5 | 27 | 29.5 | 18.5 | 6 | 0.013 |
| | G1/4 | 7669 06 13 | 8 | 12 | 30 | 32.5 | 19 | 6 | 0.019 |
| 8 | G1/8 | 7669 08 10 | 13 | 14 | 26.5 | 31 | 26 | 7 | 0.021 |
| | G1/4 | 7669 08 13 | 16 | 19 | 29 | 34 | 27.5 | 9.5 | 0.033 |
| | G3/8 | 7669 08 17 | 20 | 23 | 36 | 42 | 29 | 11.5 | 0.063 |

7668

Miniature Flow Regulator Supply, Male BSPT Thread



Technical polymer, nickel-plated brass, NBR



| ØD | C | | F | G | H min | H max | L | L1 | kg |
|----|------|----------------------------|----|------|-------|-------|------|------|-------|
| 4 | R1/8 | 7668 04 10 | 7 | 11.5 | 25 | 27.5 | 18 | 6 | 0.011 |
| | R1/8 | 7668 06 10 | 7 | 11.5 | 25 | 27.5 | 18.5 | 6 | 0.012 |
| 6 | R1/4 | 7668 06 13 | 8 | 13.5 | 27.5 | 30 | 19 | 7 | 0.019 |
| | R1/8 | 7668 08 10 | 13 | 14 | 24 | 28.5 | 26 | 7 | 0.020 |
| 8 | R1/4 | 7668 08 13 | 16 | 19 | 25 | 29 | 27.5 | 9.5 | 0.032 |
| | R3/8 | 7668 08 17 | 20 | 23 | 30 | 36 | 29 | 11.5 | 0.061 |

Pre-coated thread