


# Manually-Operated Valves

## 7800

### 3/2 Manual Switch-Operated Valve, Supply, Male BSPP and Metric Thread



Technical polymer, nickel-plated brass, NBR



ØD	C		F	F1	H	L1	L2	kg
4	M5x0.8	<a href="#">7800 04 19</a>	14	14	42	7	18.5	0.008
	G1/8	<a href="#">7800 04 10</a>	14	14	43	7	18.5	0.022
6	M5x0.8	<a href="#">7800 06 19</a>	14	14	42	7	18.5	0.009
	G1/8	<a href="#">7800 06 10</a>	14	14	43	7	20	0.023
8	G1/4	<a href="#">7800 08 10</a>	17	14	50.5	9	22	0.048
	G1/8	<a href="#">7800 08 10</a>	14	14	43	7	25	0.023
10	G1/4	<a href="#">7800 10 13</a>	17	14	50.5	9	29	0.048


For part numbers 7800 04 19 and 7800 06 19, adaptor sealing is effected by a flat PTFE seal and tightening torque is maximum 0.16 daN.m.

## 7801

### 3/2 Manual Switch-Operated Valve, Control, Male BSPP Thread



Technical polymer, nickel-plated brass, NBR




ØD	C		F	F1	H	L1	L2	kg
4	G1/8	<a href="#">7801 04 10</a>	14	14	43	7	18.5	0.023
6	G1/8	<a href="#">7801 06 10</a>	14	14	43	7	20	0.023
	G1/4	<a href="#">7801 06 13</a>	17	14	50.5	9	22	0.048
8	G1/8	<a href="#">7801 08 10</a>	14	14	43	7	25	0.026
	G1/4	<a href="#">7801 08 13</a>	17	14	50.5	9	27	0.049
10	G1/4	<a href="#">7801 10 13</a>	17	14	50.5	9	29	0.051

## 7802

### 2/2 Manual Switch-Operated Valve, Male BSPP Thread



Technical polymer, nickel-plated brass, NBR




ØD	C		F	F1	H	L1	L2	kg
4	G1/8	<a href="#">7802 04 10</a>	14	14	43	7	18.5	0.023
	G1/8	<a href="#">7802 06 10</a>	14	14	43	7	20	0.024
6	G1/4	<a href="#">7802 06 13</a>	17	14	50.5	9	22	0.050
	G1/8	<a href="#">7802 08 10</a>	14	14	43	7	25	0.024
8	G1/4	<a href="#">7802 08 13</a>	17	14	50.5	9	27	0.052
	G1/4	<a href="#">7802 10 13</a>	17	14	50.5	9	29	0.052

## 0669

### 3/2 Sleeve Valve, Female BSPP and Metric Thread



Nickel-plated brass, aluminium, NBR



C	DN		F	G	L	kg
M5x0.8	2.5	<a href="#">0669 02 19</a>	10	14	30.5	0.012
G1/8	4	<a href="#">0669 04 10</a>	14	25	48	0.050
G1/4	7	<a href="#">0669 07 13</a>	19	30	58	0.096
G3/8	10	<a href="#">0669 10 17</a>	22	35	68	0.154
G1/2	14	<a href="#">0669 14 21</a>	27	40	75	0.210
G3/4	19	<a href="#">0669 19 27</a>	32	50	83	0.324