







Brass Adaptors

0126 Plug for Compression Fitting

	Brass 	ØD		L	kg
		4	0126 04 00	10	0.001
		5	0126 05 00	10	0.003
		6	0126 06 00	10	0.003
		8	0126 08 00	11.5	0.006
		10	0126 10 00	13	0.010
		12	0126 12 00	13	0.014
		14	0126 14 00	13.5	0.020
		15	0126 15 00	13.5	0.022
		16	0126 16 00	16	0.029
		18	0126 18 00	16	0.039
		20	0126 20 00	16	0.045
		22	0126 22 00	18	0.003
		28	0126 28 00	19.5	0.108




The plug is used to blank off an outlet in a compression fitting, replacing the olive.
When an open outlet is required, simply dismantle and replace the plug with the tube olive, reusing the nut.
The plug is also reusable.

0125 Tube End Plug for Compression Fitting

	Brass 	ØD	C		F	L	L1	kg
		4	M8x1	0125 04 00	10	12	8	0.006
		6	M10x1	0125 06 00	11	13.5	9.5	0.008
		8	M12x1	0125 08 00	14	14	9	0.013
		10	M16x1.5	0125 10 00	17	18	11	0.025
		12	M18x1.5	0125 12 00	19	18	11	0.030
		14	M20x1.5	0125 14 00	22	19	11	0.041




This plug enables unused tubes to be blanked off.
The male thread on the plug has the same pitch as the female thread on the sleeve nut of a standard Parker Legris fitting.
Therefore the plug screwed into the sleeve nut blanks off the tube.
To reopen the passage, simply unscrew the plug and fit the required coupler.
No further treatment of the tube is required.

0220 Hex Head Plug with Captive Sealing Washer, Male BSPP and Metric Thread

	Brass, technical polymer 	C		F	G	H	kg
		M5x0.8	0220 19 00	8	8	5	0.002
		G1/8	0220 10 00	14	14	7.5	0.011
		G1/4	0220 13 00	17	17	7.5	0.019
		G3/8	0220 17 00	17	22	8.5	0.024
		G1/2	0220 21 00	22	27	10	0.040

Thread with pre-assembled washer.
M5: with screwdriver slot for tightening.
Maximum allowable working pressure = 20 bar.
Part number with suffix 99, maximum allowable working pressure = 250 bar, example: 0220 19 00 99.
Conforms to BNA 229 (with the exception of M5 model): BSPP thread, ISO ISO 228-1;
metric thread, ISO NFE 03-054.

0220..39 Hex Head Plug with Bi-Material Seal, Male BSPP Thread

	Brass, zinc-plated steel with NBR seal 	C		F	G	H1	kg
		G1/8	0220 10 00 39	14	14	6.5	0.012
		G1/4	0220 13 00 39	17	17	6.5	0.020
		G3/8	0220 17 00 39	17	22	8	0.025
		G1/2	0220 21 00 39	22	26	9	0.043
		G3/4	0220 27 00 39	22	32	10	0.060
		G1	0220 34 00 39	27	39.5	10.5	0.089

Plug with bi-material seal.
Bi-material washers part number 0139 can be found in Chapter 9.