







# Stainless Steel Compression Fittings




## 1866 3-Piece Reducer

	Stainless steel 316L		<b>ØD1</b>	<b>ØD2</b>		<b>F</b>	<b>kg</b>
			6	8	<a href="#">1866 06 08</a>	14	0.011
			6	10	<a href="#">1866 06 10</a>	19	0.028
				12	<a href="#">1866 06 12</a>	22	0.040
			8	10	<a href="#">1866 08 10</a>	19	0.026
				12	<a href="#">1866 08 12</a>	22	0.037
			10	16	<a href="#">1866 08 16</a>	27	0.071
				12	<a href="#">1866 10 12</a>	22	0.034
			12	16	<a href="#">1866 10 16</a>	27	0.065
				16	<a href="#">1866 12 16</a>	27	0.061




## 1824 Stainless Steel Olive

	Stainless steel 316L		<b>ØD</b>		<b>kg</b>
			6	<a href="#">1824 06 00</a>	0.001
			8	<a href="#">1824 08 00</a>	0.001
			10	<a href="#">1824 10 00</a>	0.003
			12	<a href="#">1824 12 00</a>	0.004
			16	<a href="#">1824 16 00</a>	0.005




## 1810 Stainless Steel Nut

	Stainless steel 316L		<b>ØD</b>	<b>C</b>		<b>F</b>	<b>L</b>	<b>kg</b>
			6	M10x1	<a href="#">1810 06 00</a>	13	11	0.007
			8	M12x1	<a href="#">1810 08 00</a>	14	13	0.008
			10	M16x1.5	<a href="#">1810 10 00</a>	19	15	0.017
			12	M18x1.5	<a href="#">1810 12 00</a>	22	15	0.024
			16	M22x1.5	<a href="#">1810 16 00</a>	27	17	0.041

## 1822 Barb Adaptor for Hose

	Stainless steel 316L		<b>ØD1</b>	<b>ØD2</b>		<b>ØD3</b>	<b>L</b>	<b>L1</b>	<b>ØT min</b>	<b>kg</b>
			6	7	<a href="#">1822 06 07</a>	9	37.5	22.5	6	0.006
				6	<a href="#">1822 08 06</a>	8	40	22.5	5	0.007
			8	7	<a href="#">1822 08 07</a>	9	40	22.5	6	0.007
				10	<a href="#">1822 08 10</a>	12.5	40	22.5	9	0.011
			10	7	<a href="#">1822 10 07</a>	9	43	22.5	6	0.009
				10	<a href="#">1822 10 10</a>	12.5	43	22.5	9	0.013
			12	10	<a href="#">1822 12 10</a>	12.2	43	22.5	9	0.012
				13	<a href="#">1822 12 13</a>	15	50	29.5	13	0.016

## 1827 Stainless Steel Tube Support

	Stainless steel 316L		<b>ØD1</b>	<b>ØD2</b>		<b>L</b>	<b>kg</b>
			6	4	<a href="#">1827 06 00</a>	11.5	0.001
			8	6	<a href="#">1827 08 00</a>	14	0.001
			10	8	<a href="#">1827 10 00</a>	18	0.001
			12	9	<a href="#">1827 12 09</a>	18	0.001
				10	<a href="#">1827 12 00</a>	18	0.001
			16	14	<a href="#">1827 16 00</a>	18	0.002

This tube support is necessary when using fluoropolymer tubing at all temperatures compatible with the fitting/tubing assembly.