





# ISO B Profile

## 23, 24 and 30 Series






### 9123 Coupler with Barb Connection

	Nickel-plated brass, NBR 		$\overline{\text{DN}}$	$\varnothing D$	<b>F</b>	<b>G</b>	<b>L</b>	<b>L1</b>	<b>kg</b>	
			6	9123 24 06	21	27	60	25	0.081	
			5.5	8	9123 24 08	21	27	60	25	0.082
				10	9123 24 10	21	27	60	25	0.082
			8.5	8	9123 30 08	22	30	66	25	0.098
				10	9123 30 10	22	30	66	25	0.098
			13	9123 30 13	22	30	66	25	0.103	




24 Series (DN 5.5): single shut-off = 550 Nl/min  
30 Series (DN 8.5): single shut-off = 890 Nl/min

### 9087 Probe, Straight-Through, Male BSPP Thread

	Nickel-plated steel, technical polymer 		$\overline{\text{DN}}$	<b>C</b>	<b>E</b>	<b>F</b>	<b>L</b>	<b>L1</b>	<b>kg</b>	
			5.5	G1/8	9087 23 10	9	13	39	24	0.017
			5.5	G1/4	9087 23 13	9	17	38	24	0.025
				G3/8	9087 23 17	9	19	38	24	0.032
			8.5	G1/2	9087 23 21	12	22	42	24	0.048
				G1/4	9087 30 13	9	17	42	28	0.030
			G3/8	9087 30 17	9	19	42	28	0.036	
			G1/2	9087 30 21	12	24	46	28	0.058	




Probe without shut-off  
23 Series probe (DN 5.5) compatible with 24 Series coupler (DN 5.5)

### 9086 Probe, Straight-Through, Female BSPP Thread

	Nickel-plated steel 		$\overline{\text{DN}}$	<b>C</b>	<b>E</b>	<b>F</b>	<b>L</b>	<b>L1</b>	<b>kg</b>	
			5.5	G1/8	9086 23 10	9	17	36	24	0.021
			5.5	G1/4	9086 23 13	9	17	36	24	0.025
				G3/8	9086 23 17	9	19	36	24	0.025
			8.5	G1/2	9086 23 21	12	24	39	24	0.039
				G1/4	9086 30 13	10	17	40	28	0.032
			G3/8	9086 30 17	10	19	42	28	0.035	
			G1/2	9086 30 21	12	24	43	28	0.046	




Probe without shut-off  
23 Series probe (DN 5.5) compatible with 24 Series coupler (DN 5.5)

### 9085 Probe, Straight-Through, with Barb Connection

	Nickel-plated steel 		$\overline{\text{DN}}$	$\varnothing D$	<b>L</b>	<b>L1</b>	<b>L2</b>	<b>kg</b>	
			5.5	6	9085 23 06	51	24	25	0.016
			5.5	8	9085 23 08	51	27	25	0.017
				10	9085 23 10	51	24	25	0.018
			8.5	8	9085 30 08	55	28	25	0.027
				10	9085 30 10	55	28	25	0.028
			13	9085 30 13	55	28	25	0.031	

Probe without shut-off  
23 Series probe (DN 5.5) compatible with 24 Series coupler (DN 5.5)

### 9293 Probe, Valved, Anti-Whiplash, Female BSPP Thread

	Nickel-plated steel, NBR 		$\overline{\text{DN}}$	<b>C</b>	<b>E</b>	<b>F</b>	<b>L</b>	<b>L1</b>	<b>kg</b>
			5.5	G1/4	9293 23 13	10	22	47	24

Probe with shut-off