

Midi Series

Without Shut-Off



Single Shut-Off



0172 Coupler, Female BSPP Thread

	Nickel-plated brass, NBR		DN	C		E	F	G	L	kg
			12	G3/8	0172 12 17	16	27	29	56	0.155
				G1/2	0172 12 21	16	27	29	56	0.142
Midi series: single shut-off = 2200 NI/min										

2272 Coupler, Straight-Through, Female BSPP Thread

	Nickel-plated brass, NBR		DN	C		E	F	G	L	kg
			12	G1/2	2272 12 21	10	24	29	33	0.072
				G3/4	2272 12 27	10	30	29	34.5	0.074
	G1	2272 12 34	10	36	29	34.5	0.087			

2511 Coupler with Barb Connection for Hose

	Nickel-plated brass, NBR		DN	ØD	ØD1		G	L	L1	kg
			12	13.5	2511 12 12	29	75	32	0.146	
			12	15	2511 12 15	29	75	32	0.147	
	19	20.5	2511 12 19	29	81	38	0.159			
Midi series: single shut-off = 2200 NI/min										

2297 Coupler, Straight-Through, with Barb Connection for Hose

	Nickel-plated brass, NBR		DN	ØD	ØD1		G	L	L1	kg
			12	13.5	2297 12 12	29	51	27	0.073	
			12	15	2297 12 15	29	51	27	0.076	
	19	20.5	2297 12 19	29	57	33	0.090			

2294 Probe, Straight-Through, Male BSPP Thread


	Nickel-plated brass		DN	C		E	F	L	kg	
			12	G3/8	2294 12 17	6	22	31.5	0.031	
				G1/2	2294 12 21	9.5	22	37	0.044	
				G3/4	2294 12 27	13.5	27	41	0.068	
	G1	2294 12 34	10.5	34	36	0.072				
Probe without shut-off										

Midi Series

Without Shut-Off



Single Shut-Off



0196 Probe, Straight-Through, Female BSPP Thread

	Nickel-plated brass		$\overline{\text{DN}}$	C		E	F	L	kg
			12	G1/4	0196 12 13	12	17	16	0.027
				G3/8	0196 12 17	12	21	15	0.034
				G1/2	0196 12 21	14	26	17	0.050
Probe without shut-off									

2296 Probe, Straight-Through, Female BSPP Thread

	Nickel-plated brass		$\overline{\text{DN}}$	C		E	G	L	kg
			12	G1/2	2296 12 21	11	24	31.5	0.031
				G3/4	2296 12 27	11	30	38	0.058
				G1	2296 12 34	11	36	36.5	0.058
Probe without shut-off									

0195 Probe, Straight-Through, with Barb Connection for Flexible Tubing

	Nickel-plated brass		$\overline{\text{DN}}$	ØD	ØD1		F	L	kg
			12	7	9	0195 07 00	17	29.5	0.026
				10	12.2	0195 10 00	17	29.5	0.028
				13	15.2	0195 13 00	17	29.5	0.030
				16	18.5	0195 16 00	21	36.5	0.048
Probe without shut-off									

2295 Probe, Straight-Through, with Barb Connection for Flexible Hose

	Nickel-plated brass		$\overline{\text{DN}}$	ØD	ØD1		G	L	L1	kg
			12	12	13.5	2295 12 12	17	48	27	0.026
				15	16.5	2295 12 15	18	48	27	0.034
				19	20.5	2295 12 19	24	57	33	0.053
Probe without shut-off										

2293 Y Coupler, Straight-Through

	Nickel-plated brass, NBR		$\overline{\text{DN}}$		G	H	kg
			12	2293 12 00	29	27	0.139
Probe without shut-off Midi Series: straight-through = 2200 NI/min							

Midi Series




Without Shut-Off






Single Shut-Off






2270 Coupler with Tap, Male BSP Thread

	Nickel-plated brass, NBR 	$\overline{\text{DN}}$ C 	F	G	H	M	kg	
			12	G1/2	2270 21 00	28	29	40.5
Flow = 2200 NI/min								




2203 Plug

	Nickel-plated brass 	$\overline{\text{DN}}$ 	G	L	kg
			12	2203 12 00	20




2292 Universal Coupler Adaptor

	Nickel-plated brass, NBR 	$\overline{\text{DN}}$ 	G	L	kg
			12	2292 12 00	29
Without shut-off This adaptor provides interchangeability with numerous components (especially watering accessories).					




2398 Universal Probe Adaptor

	Nickel-plated brass, NBR 	$\overline{\text{DN}}$ 	G	L	L1	L2	kg
			12	2398 12 01	20	43	19
This adaptor provides interchangeability with numerous components (especially watering accessories).							

2299 Water Pistol

	Zamak, Nickel-plated brass, NBR 	$\overline{\text{DN}}$ 	H	L	kg
			12	2299 12 01	140
This pistol allows independent control of: - the flow rate (trigger) - type of jet (adjustable to a fine mist) by the adjustable Probe					

2299 Adjustable Nozzle

	Nickel-plated brass, NBR 	$\overline{\text{DN}}$ 	L	kg
			12	2299 12 20
This nozzle allows adjustment of the spray.				