


Stainless Steel German Profile

X20 Series



9201 Coupler, Male BSPP and Metric Thread

	Stainless steel 316L, FKM		C	E	F	G	L	kg		
				2.7	M5x0.8	9201X20 19	5	9	10	26
				G1/8	9201X20 10	7	11	10	28	0.011

X20 Series (DN 2.7) : single shut-off = 165 NI/min
X20 Series (DN 2.7) : double shut-off = 130 NI/min

9214 Coupler, Female BSPP and Metric Thread

	Stainless steel 316L, FKM		C	E	F	G	L	kg		
				2.7	M5x0.8	9214X20 19	5	9	10	26
				G1/8	9214X20 10	7	12	10	28	0.012

X20 Series (DN 2.7) : single shut-off = 165 NI/min
X20 Series (DN 2.7) : double shut-off = 130 NI/min

9287 Probe, Valved, Male BSPP and Metric Thread

	Stainless steel 316L, FKM		C	E	F	L	L1	kg		
				2.7	M5x0.8	9287X20 19	5	9	28	10
				G1/8	9287X20 10	7	11	30	10	0.009

Probe with shut-off

9087 Probe, Straight-Through, Male BSPP and Metric Thread

	Stainless steel 316L		C	E	F	L	L1	kg		
				2.7	M5x0.8	9087X20 19	5	7	18	10
				G1/8	9087X20 10	7	11	20	10	0.015

Probe without shut-off

9286 Probe, Valved, Female BSPP and Metric Thread

	Stainless steel 316L, FKM		C	E	F	L	L1	kg		
				2.7	M5x0.8	9286X20 19	5	9	26	10
				G1/8	9286X20 10	7	12	30	10	0.014

Probe with shut-off

9086 Probe, Straight-Through, Female BSPP and Metric Thread

	Stainless steel 316L		C	E	F	L	L1	kg		
				2.7	M5x0.8	9086X20 19	5	7	17	10
				G1/8	9086X20 10	7	12	19	10	0.005

Probe without shut-off