





Stainless Steel German Profile




X21 Series






9201 Coupler, Male BSPP Thread

	Stainless steel 316L, FKM 	DN C 	E F G L kg	5 G1/8 9201X21 10 7 14 16 36 0.026	
				G1/4 9201X21 13 9 17 16 38 0.034	
X21 Series (DN 5): single shut-off = 560 NI/min X21 Series (DN 5): double shut-off = 310 NI/min					




9214 Coupler, Female BSPP Thread

	Stainless steel 316L, FKM 	DN C 	E F G L kg	5 G1/8 9214X21 10 9 14 16 36 0.027	
				G1/4 9214X21 13 9 17 16 38 0.037	
X21 Series (DN 5): single shut-off = 560 NI/min X21 Series (DN 5): double shut-off = 310 NI/min					




9287 Probe, Valved, Male BSPP Thread

	Stainless steel 316L, FKM 	DN C 	E F L L1 kg	5 G1/8 9287X21 10 7 14 40 14 0.021	
				G1/4 9287X21 13 9 17 42 14 0.030	
Probe with shut-off					




9087 Probe, Straight-Through, Male BSPP Thread

	Stainless steel 316L 	DN C 	E F L L1 kg	5 G1/8 9087X21 10 7 14 25 14 0.011	
				G1/4 9087X21 13 9 17 28 14 0.018	
Probe without shut-off					

9286 Probe, Valved, Female BSPP Thread

	Stainless steel 316L, FKM 	DN C 	E F L L1 kg	5 G1/8 9286X21 10 7 14 40 14 0.024	
				G1/4 9286X21 13 9 17 42 14 0.033	
Probe with shut-off					

9086 Probe, Straight-Through, Female BSPP Thread

	Stainless steel 316L 	DN C 	E F L L1 kg	5 G1/8 9086X21 10 8 14 25 14 0.013	
				G1/4 9086X21 13 9 17 25 14 0.017	
Probe without shut-off					