

Mini Series

Single Shut-Off



Double Shut-Off



0171 Coupler, Male BSPT and Parallel Metric Thread

	<p>Technical polymer, nickel-plated brass, NBR</p>		<p>C</p>		<p>Colour</p>	<p>F L kg</p>					
							2	M7x1	0171 02 55 01		10 21 0.007
								R1/8	0171 02 10 01		10 21 0.010
								R1/8	0171 02 10 02		10 21 0.010
								R1/8	0171 02 10 03		10 21 0.010
								R1/8	0171 02 10 04		10 21 0.010
	R1/8	0171 02 10 05		10 21 0.010							

Single shut-off
Mini Series (DN 2): single shut-off = 165 NL/min

0171 Coupler, Straight-Through, Male BSPT Thread

	<p>Technical polymer, nickel-plated brass, NBR</p>		<p>C</p>		<p>Colour</p>	<p>F G L kg</p>					
							3	R1/8	0171 03 10 01		13 17 24.5 0.020
								R1/8	0171 03 10 02		13 17 24.5 0.020
								R1/8	0171 03 10 03		13 17 24.5 0.020
								R1/8	0171 03 10 04		13 17 24.5 0.020
								R1/8	0171 03 10 05		13 17 24.5 0.020

Straight-through

0183 Probe, Valved, Male BSPT Thread

	<p>Nickel-plated brass, NBR</p>		<p>C</p>		<p>F L kg</p>

Probe with shut-off

0184 Probe, Straight-Through, Male BSPT Thread

	<p>Nickel-plated brass</p>		<p>C</p>		<p>F L kg</p>


Probe without shut-off

0181 Probe without Shut-off, Male BSPT Thread

	<p>Nickel-plated brass</p>		<p>ØD ØD1</p>		<p>L L1 kg</p>

Probe without shut-off

Mini Series



0181 Probe, Straight-Through with Barb Connection for Polyamide (PA) Tubing

	Nickel-plated brass		ØD ØD1	L	kg			
			<table border="1"> <tr> <td>3</td> <td>4</td> <td>4.7</td> <td>0181 04 06</td> <td>19</td> <td>0.005</td> </tr> </table>	3	4	4.7	0181 04 06	19
3	4	4.7	0181 04 06	19	0.005			
Probe without shut-off								

0180 Probe, Straight-Through with Barb Connection for Flexible Tubing

	Nickel-plated brass		ØD ØD1	L	kg									
			<table border="1"> <tr> <td>3</td> <td>4</td> <td>6</td> <td>0180 04 00</td> <td>19</td> <td>0.007</td> </tr> <tr> <td></td> <td>5</td> <td>6.5</td> <td>0180 05 00</td> <td>19</td> <td>0.007</td> </tr> </table>	3	4	6	0180 04 00	19	0.007		5	6.5	0180 05 00	19
3	4	6	0180 04 00	19	0.007									
	5	6.5	0180 05 00	19	0.007									
Probe without shut-off														

3150 Probe, Straight-Through with LF 3000® Push-In Connection

	Nickel-plated brass, NBR		ØD	G	L	L1	kg				
			<table border="1"> <tr> <td>3</td> <td>4</td> <td>3150 00 61</td> <td>8.5</td> <td>39</td> <td>18</td> <td>0.008</td> </tr> </table>	3	4	3150 00 61	8.5	39	18	0.008	
3	4	3150 00 61	8.5	39	18	0.008					
Probe without shut-off											