

Stainless Steel Adaptors

1863 Reducer, Male BSPT/Female BSPP Thread

Image	Stainless steel 316L	C1	C2	Icon	F	L	kg
		R1/4	G1/8	1863 13 10	14	16	0.008
		R3/8	G1/8	1863 17 10	17	16.5	0.019
			G1/4	1863 17 13	17	16.5	0.011
		R1/2	G1/4	1863 21 13	22	21	0.036
			G3/8	1863 21 17	22	21	0.023
		R3/4	G1/2	1863 27 21	27	25.5	0.045
		R1	G3/4	1863 34 27	36	28.5	0.083

1872 Reducer, Male/Female NPT Thread

Image	Stainless steel 316L	C1	C2	Icon	F	L	kg
		NPT1/4	NPT1/8	1872 14 11	14	16	0.010
		NPT3/8	NPT1/8	1872 18 11	19	16.5	0.023
			NPT1/4	1872 18 14	19	16.5	0.016
		NPT1/2	NPT1/4	1872 22 14	22	21	0.039
			NPT3/8	1872 22 18	22	21	0.028

1861 Increaser, Male BSPT/Female BSPP Thread

Image	Stainless steel 316L	C1	C2	Icon	E	F	L	kg
		R1/8	G1/4	1861 10 13	11	17	24	0.022
			G3/8	1861 10 17	11.5	22	25	0.038
		R1/4	G3/8	1861 13 17	11.5	22	28.5	0.042
			G1/2	1861 13 21	15	27	32.5	0.068
		R3/8	G1/2	1861 17 21	15	27	33	0.070
		R1/2	G3/4	1861 21 27	16.5	32	38	0.093
		R3/4	G1	1861 27 34	19	41	43.5	0.182

1873 Increaser, Male/Female NPT Thread

Image	Stainless steel 316L	C1	C2	Icon	E	F	L	kg
		NPT1/8	NPT1/4	1873 11 14	14	17	25	0.024
			NPT3/8	1873 11 18	14	22	25	0.039
		NPT1/4	NPT3/8	1873 14 18	14	22	28.5	0.042
			NPT1/2	1873 14 22	17.5	27	31	0.065
		NPT3/8	NPT1/2	1873 18 22	17.5	27	31.5	0.066

1821 Equal and Unequal Adaptor, Male BSPT Thread

Image	Stainless steel 316L	C1	C2	Icon	F	L	kg
		R1/8	R1/8	1821 10 10	12	19	0.009
			R1/4	1821 13 10	14	23.5	0.016
		R1/4	R1/4	1821 13 13	14	27	0.019
			R1/4	1821 17 13	17	27.5	0.024
		R3/8	R3/8	1821 17 17	17	28	0.024
			R3/8	1821 21 17	22	32.5	0.042
		R1/2	R1/2	1821 21 21	22	36	0.048
			R1/2	1821 27 21	27	41	0.079
		R3/4	R3/4	1821 27 27	27	42	0.088
			R3/4	1821 34 27	36	46	0.141
		R1	R1	1821 34 34	36	48	0.146