







Anodised Aluminium Manifolds




3310 In-Line Manifold

	Treated aluminium, NBR			ØD	C		Number of Outlets	E	H	L	L1	N	kg
	4	G1/4		3310 04 13	8		10	33	114	104	11.5	0.175	
	6	G1/4		3310 06 13	8		10	33	114	104	12.5	0.169	
	8	G3/8		3310 08 17	6		12	33	114	104	15	0.156	
	10	G1/2		3310 10 21	6		14	48	130	119.5	17	0.348	
	12	G1/2		3310 12 21	6		14	45	117	107	20.5	0.370	




3311 Manifold, Female BSPP and Metric Thread

	Treated aluminium			C1	C2		Number of Outlets	H	H1	H2	K	L	L1	N	ØT	kg
	G1/8	M5x0.8		3311 19 10 07	7		3.5	20	8.5	15	95	80	11	4.4	0.067	
	G1/8			3311 10 13 02	2		4.5	30	15	20	61	50	30	5	0.079	
	G1/8			3311 10 13 03	3		4.5	30	15	20	91	30	30	5	0.121	
	G1/4	G1/8			3311 10 13 04		4	4.5	30	15	20	121	60	30	5	0.165
		G1/8			3311 10 13 05		5	4.5	30	15	20	151	90	30	5	0.209
		G1/8			3311 10 13 06		6	4.5	30	15	20	181	120	30	5	0.244
	G1/4	G1/4			3311 13 17 02		2	5.5	30	11	20	74	61	36	6.5	0.076
		G1/4			3311 13 17 03		3	6	30	11	20	110	36	36	6.5	0.121
		G1/4			3311 13 17 04		4	6	30	11	20	146	72	36	6.5	0.144
	G3/8	G1/4			3311 13 17 05		5	6	30	11	20	182	108	36	6.5	0.212
		G1/4			3311 13 17 06		6	6	30	11	20	218	144	36	6.5	0.265

3312 Cross Manifold, Female BSPP and Metric Thread

	Treated aluminium			C		H	K	L	L1	N	ØT	kg
	M5x0.8	3312 00 19		20		10	20	12	12	4.5	0.010	
	G1/8	3312 00 10		30		16	30	23	22	4.5	0.029	
	G1/4	3312 00 13		40		20	40	30	27	5.5	0.066	
	G3/8	3312 00 17		50		25	50	38	39	6.5	0.126	
	G1/2	3312 00 21		50		25	50	38	39	6.5	0.101	

3313 Double Manifold, Female BSPP Thread

	Treated aluminium			C1	C2		Number of Outlets	H	H1	H2	K	L	L1	N	ØT	kg
	G1/4	G1/8			3313 10 13 02		2x2	4.5	30	15	20	61	50	30	5	0.075
		G1/8			3313 10 13 03		2x3	4.5	30	15	20	91	30	30	5	0.115
		G1/8			3313 10 13 04		2x4	4.5	30	15	20	121	60	30	5	0.151
	G1/4	G1/8			3313 10 13 05		2x5	4.5	30	15	20	151	90	30	5	0.194
		G1/4			3313 13 17 02		2x2	6	40	20	20	74	61	36	6.5	0.109
		G1/4			3313 13 17 03		2x3	6	40	20	20	110	36	36	6.5	0.179
	G3/8	G1/4			3313 13 17 04		2x4	6	40	20	20	146	72	36	6.5	0.238
		G1/4			3313 13 17 05		2x5	6	40	20	20	182	108	36	6.5	0.286
		G1/4			3313 13 21 03		2x3	6	40	20	28	116	36	36	6.5	0.222
	G1/2	G1/4			3313 13 21 04		2x4	6	40	20	28	152	72	36	6.5	0.295
		G1/4			3313 13 21 05		2x5	6	40	20	28	188	108	36	6.5	0.369