

# Brass Plugs

## 0205 Internal Hexagon Head Plug, Male BSPT Thread

	Brass		<b>C</b>		<b>E1</b>	<b>E2 min</b>	<b>E2 max</b>	<b>F</b>	<b>G</b>	<b>H</b>	<b>kg</b>
			R1/8	<a href="#">0205 10 00</a>	6	3.1	4.9	5	9.7	8	0.003
			R1/4	<a href="#">0205 13 00</a>	8	4.7	7.3	6	13.2	10	0.007
			R3/8	<a href="#">0205 17 00</a>	8	5.1	7.7	8	16.7	11	0.013
			R1/2	<a href="#">0205 21 00</a>	8	6.4	10	10	21	13	0.026
			R3/4	<a href="#">0205 27 00</a>	11	7.7	11.3	14	26.4	17	0.054
			R1	<a href="#">0205 34 00</a>	13	8.1	12.7	17	33.2	19	0.094
			R1¼	<a href="#">0205 42 00</a>	14	10.4	15	22	41.9	22	0.176
			R1½	<a href="#">0205 49 00</a>	14	10.4	15	24	47.8	22	0.246
			R2	<a href="#">0205 48 00</a>	16	13.6	18.2	30	59.6	25	0.431
			For BSPT plug from 1/2" - 1½" inclusive: Conforms to DIN 906 Thread: EN 10226-1								

## 0205 Internal Hexagon Head Plug, Male NPT Thread

	Brass		<b>C</b>		<b>E1</b>	<b>E2 min</b>	<b>E2 max</b>	<b>F</b>	<b>G</b>	<b>H</b>	<b>kg</b>
			NPT1/8	<a href="#">0205 11 00</a>	6	3.2	5	5	10.2	8	0.003
			NPT1/4	<a href="#">0205 14 00</a>	8	4.4	7.2	6	13.6	10	0.008
			NPT3/8	<a href="#">0205 18 00</a>	8	4.7	7.5	8	17	11	0.014
			NPT1/2	<a href="#">0205 22 00</a>	8	6.3	9.9	10	21.2	13	0.026
			NPT3/4	<a href="#">0205 28 00</a>	11	6.8	10.4	14	26.6	17	0.052
			NPT1	<a href="#">0205 35 00</a>	13	8	12.4	17	33.2	19	0.091

## 0209 Square Head Plug, Male BSPT Thread

	Brass		<b>C</b>		<b>E1</b>	<b>E2 min</b>	<b>E2 max</b>	<b>G</b>	<b>H</b>	<b>J</b>	<b>kg</b>
			R1/8	<a href="#">0209 10 00</a>	6	3.1	4.9	9.7	16	6	0.007
			R1/4	<a href="#">0209 13 00</a>	8	4.7	7.3	13.2	18	8	0.014
			R3/8	<a href="#">0209 17 00</a>	10	5.1	7.7	16.7	20	10	0.025
			R1/2	<a href="#">0209 21 00</a>	11	6.4	10	21	22	13	0.047
			R3/4	<a href="#">0209 27 00</a>	15	7.7	11.3	26.4	28	17	0.097
			R1	<a href="#">0209 34 00</a>	18	8.1	12.7	33.2	32	19	0.170
			Conforms to DIN 906 Thread: EN 10226-1								

## 0220 Hex Head Plug, Male BSPP and Metric Thread

	Brass, technical polymer		<b>C</b>		<b>F</b>	<b>G</b>	<b>H1</b>	<b>kg</b>
			M5x0.8	<a href="#">0220 19 00</a>	8	8	5	0.002
			G1/8	<a href="#">0220 10 00</a>	14	14	7.5	0.011
			G1/4	<a href="#">0220 13 00</a>	17	17	7.5	0.019
			G3/8	<a href="#">0220 17 00</a>	17	22	8.5	0.024
			G1/2	<a href="#">0220 21 00</a>	22	27	10	0.040
			Pre-assembled polyamide washer M5: with screwdriver slot for tightening Maximum allowable working pressure = 20 bar Part number with suffix 99, maximum allowable working pressure = 250 bar, example: 0220 19 00 99 Conforms to BNA 229 (with the exception of M5 model), BSPP thread, ISO ISO 228-1, Parallel, metric thread, ISO NFE 03-054					

## 0200 Hex Head Plug, Male BSPP and Metric Thread

	Brass		<b>C</b>		<b>E</b>	<b>F</b>	<b>G</b>	<b>H1</b>	<b>H2</b>	<b>kg</b>
			M6x1	<a href="#">0200 52 00</a>	6	10	10	4	3.5	0.004
			M8x1.25	<a href="#">0200 57 00</a>	7	13	13	4	3.5	0.007
			M10x1	<a href="#">0200 60 00</a>	8	14	14	5	4.5	0.011
			M12x1	<a href="#">0200 65 00</a>	9	17	17	5	4.5	0.018
			M12x1.25	<a href="#">0200 66 00</a>	9	17	17	5	4.5	0.017
			G1/8	<a href="#">0200 10 00</a>	7	14	13.7	5.5	4	0.011
			G1/4	<a href="#">0200 13 00</a>	8.5	17	16.7	5.5	4	0.019