


Brass Plugs


0201

Hex Head Plug with Collar, Male BSP and Metric Thread

C		E		F	G	H1	H2	kg
		mm	in	mm	mm	mm	mm	
M16x1.5	0201 75 00	10	17	22	6.5	5		0.025
M18x1.5	0201 78 00	10	17	24	7	5		0.026
M20x1.5	0201 80 00	10	17	26	7.5	5		0.031
M22x1.5	0201 82 00	10	22	30	7.5	5		0.044
M24x1.5	0201 83 00	10	22	32	7.5	5		0.046
M24x2	0201 92 00	10	22	32	7.5	5		0.046
M30x2	0201 88 00	11	27	38	8.5	6		0.075
G3/8	0201 17 00	10	17	21.7	6.5	4.5		0.024
G1/2	0201 21 00	10	22	26.7	7.5	5		0.041
G3/4	0201 27 00	11	22	31.7	8.5	6		0.057
G1	0201 34 00	11	27	39.7	8.5	6		0.087
G1¼	0201 42 00	12	30	49.7	10	7		0.142

0202

Internal Hexagon Head Plug with Collar, Male Metric Thread

C		E		F	G	H	H1	kg
		mm	in	mm	mm	mm	mm	
M12x1	0202 65 00	9	6	17	11	8		0.009
M12x1.25	0202 66 00	9	6	17	11	8		0.009
M14x1.5	0202 71 00	10	6	19	13	10		0.015
M16x1.5	0202 75 00	10	8	22	13	10		0.020
M18x1.5	0202 78 00	10	10	24	13	10		0.022
M20x1.5	0202 80 00	10	12	26	13	10		0.025
M22x1.5	0202 82 00	10	12	30	13	10		0.034
M27x2	0202 86 00	11	17	35	15	11		0.053
M30x2	0202 88 00	11	19	38	15	11		0.062

Parallel metric threads, ISO standard NFE 03-054