

Steel Plugs

0206 Internal Hexagon Head Plug, Male BSPT Thread

	Steel		C		E1	E2 min	E2 max	F	G	H	kg
			R1/8	0206 10 00	6	3.1	4.9	5	9.7	8	0.003
			R1/4	0206 13 00	8	4.7	7.3	6	13.2	10	0.007
			R3/8	0206 17 00	8	5.1	7.7	8	16.7	11	0.012
			R1/2	0206 21 00	8	6.4	10	10	21	13	0.023
			R3/4	0206 27 00	11	7.7	11.3	14	26.4	17	0.048
			R1	0206 34 00	13	8.1	12.7	17	33.2	19	0.086
			R1¼	0206 42 00	14	10.4	15	22	41.9	22	0.166
			R1½	0206 49 00	14	10.4	15	24	47.8	22	0.222
<p>For BSPT plugs, from 1/2" - 1½" inclusive Conforms to DIN 906 Thread, conforms to EN 10226-1</p>											

0206 Internal Hexagon Head Plug, Male NPT Thread

	Steel		C		E1	E2 min	E2 max	F	G	H	kg
			NPT1/16	0206 08 00	6	3.8	6.4	4	7.8	7	0.002
			NPT1/8	0206 11 00	6	3.2	5	5	10.2	8	0.003
			NPT1/4	0206 14 00	8	4.4	7.2	6	13.6	10	0.007
			NPT3/8	0206 18 00	8	4.7	7.5	8	17	11	0.012
			NPT1/2	0206 22 00	8	6.3	9.9	10	21.2	13	0.024
			NPT3/4	0206 28 00	11	6.8	10.4	14	26.6	17	0.047
			NPT1	0206 35 00	13	8	12.4	17	33.2	19	0.083

0210 Hex Head Plug, Male BSPP and Metric Thread

	Steel		C		E	F	G	H	kg
			M8x1.25	0210 57 00	8	14	12	15	0.010
			M10x1	0210 60 00	8	14	14	15	0.013
			M12x1.25	0210 66 00	11	17	17	18	0.021
			G1/8	0210 10 00	8	14	14	15	0.012
			M14x1.25	0210 70 00	11	19	19	20	0.032
			G1/4	0210 13 00	12	19	18	21	0.031
			G3/8	0210 17 00	12	22	22	21	0.046
			G1/2	0210 21 00	14	27	26	24	0.078
			G3/4	0210 27 00	16	32	32	27	0.134
			G1	0210 34 00	18	41	39	33	0.269
			G1¼	0210 42 00	20	50	49	35	0.441
<p>Profile of head undercut conforms to DIN 3852-1; form D/E BSPP threads, ISO 228-1 Parallel metric threads, NFE 03-054</p>									

0216 Hex Head Plug, Male BSPT Thread

	Steel		C		F	H	kg
			R1/8	0216 10 00	13	16	0.012
			R1/4	0216 13 00	17	19	0.023
			R3/8	0216 17 00	19	21	0.038
			R1/2	0216 21 00	22	23	0.060
<p>BSPT thread conforms to EN 10226-1</p>							

0216 Hex Head Plug, Male NPT Thread

	Steel		C		F	H	kg
			NPT1/8	0216 11 00	13	16	0.012
			NPT1/4	0216 14 00	17	19	0.024
			NPT3/8	0216 18 00	19	21	0.038
			NPT1/2	0216 22 00	22	23	0.060