






# Sealing Accessories




## 0605 Fluoropolymer Tape

	FKM		<b>kg</b>
		<b>0605 12 12</b>	0.012
<p>Can be used for temperatures from - 250°C to +260°C.            Chemically inert and resistant to gases, acids, solvents, hydrocarbons, oils, alkalines, steam etc.            Non-toxic, waterproof, self-lubricating.            In accordance with CFR21.            Can be used on all materials.            Used to facilitate the preparation of leak-free threaded joints.            Supplied on a reel, length = 12 m; width = 12.7 mm; thickness 0.08 mm.</p>			

## 0602 Captive Sealing Washer

	Technical polymer	<b>C</b>		<b>G1</b>	<b>G2</b>	<b>K</b>	<b>kg</b>																																									
		<table border="1"> <tr> <td>M5x0.8</td> <td><b>0602 29 93 15</b></td> <td>5.2</td> <td>7.8</td> <td>1.5</td> <td>0.001</td> </tr> <tr> <td>G1/8</td> <td><b>0602 23 10 20</b></td> <td>10.3</td> <td>14</td> <td>2</td> <td>0.001</td> </tr> <tr> <td>G1/4</td> <td><b>0602 23 11 20</b></td> <td>13.7</td> <td>17.5</td> <td>2</td> <td>0.001</td> </tr> <tr> <td>G3/8</td> <td><b>0602 23 12 20</b></td> <td>17.2</td> <td>21</td> <td>2</td> <td>0.001</td> </tr> <tr> <td>G1/2</td> <td><b>0602 23 13 20</b></td> <td>21.5</td> <td>25.5</td> <td>2.5</td> <td>0.002</td> </tr> <tr> <td>G3/4</td> <td><b>0602 27 32 20</b></td> <td>27</td> <td>32</td> <td>2.5</td> <td>0.001</td> </tr> <tr> <td>G1</td> <td><b>0602 30 60 20</b></td> <td>33.8</td> <td>39</td> <td>3</td> <td>0.001</td> </tr> </table>	M5x0.8	<b>0602 29 93 15</b>	5.2	7.8	1.5	0.001	G1/8	<b>0602 23 10 20</b>	10.3	14	2	0.001	G1/4	<b>0602 23 11 20</b>	13.7	17.5	2	0.001	G3/8	<b>0602 23 12 20</b>	17.2	21	2	0.001	G1/2	<b>0602 23 13 20</b>	21.5	25.5	2.5	0.002	G3/4	<b>0602 27 32 20</b>	27	32	2.5	0.001	G1	<b>0602 30 60 20</b>	33.8	39	3	0.001	Maximum allowable working pressure: 20 bar			
M5x0.8	<b>0602 29 93 15</b>	5.2	7.8	1.5	0.001																																											
G1/8	<b>0602 23 10 20</b>	10.3	14	2	0.001																																											
G1/4	<b>0602 23 11 20</b>	13.7	17.5	2	0.001																																											
G3/8	<b>0602 23 12 20</b>	17.2	21	2	0.001																																											
G1/2	<b>0602 23 13 20</b>	21.5	25.5	2.5	0.002																																											
G3/4	<b>0602 27 32 20</b>	27	32	2.5	0.001																																											
G1	<b>0602 30 60 20</b>	33.8	39	3	0.001																																											

## 0139 Bi-Material Captive Sealing Washer

	Zinc-plated steel with NBR seal	<b>C</b>		<b>G</b>	<b>K</b>	<b>K1</b>	<b>kg</b>																																			
		<table border="1"> <tr> <td>G1/8</td> <td><b>0139 10 00</b></td> <td>14</td> <td>1</td> <td>1.7</td> <td>0.001</td> </tr> <tr> <td>G1/4</td> <td><b>0139 13 00</b></td> <td>17</td> <td>1</td> <td>1.7</td> <td>0.001</td> </tr> <tr> <td>G3/8</td> <td><b>0139 17 00</b></td> <td>22</td> <td>1.2</td> <td>2.1</td> <td>0.001</td> </tr> <tr> <td>G1/2</td> <td><b>0139 21 00</b></td> <td>26</td> <td>1.6</td> <td>2.5</td> <td>0.002</td> </tr> <tr> <td>G3/4</td> <td><b>0139 27 00</b></td> <td>32</td> <td>1.5</td> <td>2.5</td> <td>0.003</td> </tr> <tr> <td>G1</td> <td><b>0139 34 00</b></td> <td>39.6</td> <td>1.7</td> <td>2.6</td> <td>0.003</td> </tr> </table>	G1/8	<b>0139 10 00</b>	14	1	1.7	0.001	G1/4	<b>0139 13 00</b>	17	1	1.7	0.001	G3/8	<b>0139 17 00</b>	22	1.2	2.1	0.001	G1/2	<b>0139 21 00</b>	26	1.6	2.5	0.002	G3/4	<b>0139 27 00</b>	32	1.5	2.5	0.003	G1	<b>0139 34 00</b>	39.6	1.7	2.6	0.003	Maximum allowable working pressure: 250 bar			
G1/8	<b>0139 10 00</b>	14	1	1.7	0.001																																					
G1/4	<b>0139 13 00</b>	17	1	1.7	0.001																																					
G3/8	<b>0139 17 00</b>	22	1.2	2.1	0.001																																					
G1/2	<b>0139 21 00</b>	26	1.6	2.5	0.002																																					
G3/4	<b>0139 27 00</b>	32	1.5	2.5	0.003																																					
G1	<b>0139 34 00</b>	39.6	1.7	2.6	0.003																																					

Technical characteristics of captive seals **0602**

Tightening torque



	M5x0.8	G1/8	G1/4	G3/8	G1/2	G3/4	G1
Min. Torque in daN.m	0.06	0.08	0.3	0.5	1	1.2	1.9
Max. Torque daN.m	0.16	0.8	1.2	3	3.5	6	9