


SUBMERSIBLE

50PU2

- 2" (50mm) outlet
 - 35mm passage
 - free-standing
 - guide rail option
 - manual
 - automatic
 - 110 volts
 - 230 volts
 - 400 volts
- ✓ Fixed Installations
 - ✓ Screened effluent
 - ✓ Processing
 - ✓ Light sewage
 - ✓ Water Features

The **50PU2** series of sewage pumps, have 304 stainless steel motor frames and hi-tech plastic upper and lower casings for excellent corrosion and wear resistant performance. For ultimate safety, and to conform to Water Authority recommendations, all automatic versions have an integral transformer to give low voltage (24V) at the float end. The floats have a "teardrop" shape to minimise false starting of the motor caused by water turbulence. Long term, trouble free operation is enhanced further with an integrated vent valve to prevent air locking. The 403 stainless steel shaft is fitted with an ultra hardwearing, silicon carbide, double mechanical seal (in an oil chamber), and a vortex impeller to give excellent performance when pumping suspended soft solids and fibrous material. An auto-coupling set is available as an optional extra to allow the fitting of guide rails on all models. The high specification makes these units suitable for use by utilities and industry for portable use or fixed installations. Supplied with 10 metres of heavy duty, H07RN-F rubber power cable.

MEDIUM DUTY SEWAGE – VORTEX IMPELLER



50PUA2.4S automatic



50PU2.4S manual



ACCESSORIES

- Hoses page 91
- Swing valves page 102
- Hose tails page 94

model	Manual or Auto	outlet (BSPF)	kW	volt	flow (l/min)	head (mtrs)	free passage (mm)	w x l x h (mm)	max. on level (mm)	off level (mm)	weight (kgs)
50PU2.4S	M	2"	0.40	110	270	9.5	35	162x236x360	-	-	7.1
50PU2.4S	M	2"	0.40	230	270	9.5	35	162x236x360	-	-	7.1
50PU2.4	M	2"	0.40	400	270	9.5	35	162x236x360	-	-	7.0
50PUA2.4S	A	2"	0.40	110	270	9.5	35	173x236x374	607	115	7.6
50PUA2.4S	A	2"	0.40	230	270	9.5	35	173x236x374	607	115	7.6
50PUA2.4	A	2"	0.40	400	270	9.5	35	173x236x374	607	115	7.5
50PU2.75S	M	2"	0.75	230	355	12.5	35	162x236x380	-	-	8.4
50PUA2.75S	A	2"	0.75	230	355	12.5	35	173x236x394	627	115	8.9
50PU2.75	M	2"	0.75	400	355	12.5	35	162x236x374	-	-	8.3
50PUA2.75	A	2"	0.75	400	355	12.5	35	173x236x388	621	115	8.8

Optional extra: auto coupling set for guide rails

Optional extra: 2" BSPF x 50mm hose tail (polypropylene)