



LIGHTWEIGHT & HIGH PRESSURE PERFORMANCE PUMPS

Lightweight portability and high pressure are the key attributes of the WX and WH range respectively. Despite their diminutive size they are all capable of an 8m suction head, generating impressive pressure and use tool-free, quick-release hose couplings.

Superbly portable, the WX models are particularly compact and lightweight for easy transfer to where ever they are needed. A unique 360° lubrication system allows the WX10 to carry on working at virtually any angle without spilling oil or affecting the pump's optimal lubrication, as well as ensuring trouble-free operation after storage or transportation.

A powerful GX160 engine, together with a strong cast iron impeller for high abrasion resistance, are at the heart of the WH range. Producing exceptionally high pressure and head lift, the self-priming pumps are ideal for sprinkling, jetting, long-hose irrigation or fire fighting applications.



Domestic Use



Professional Use



WX 10



WX 15 *



WH 15 *



WH 20

For feature and technology symbol glossary see page 30

For full water pump model specifications see page 35-36

Max output capacity

Inlet/outlet diameter - thread type	
Total head	
Suction head	
Pressure	
Debris size capacity	
Fuel tank capacity	
Operating time	
Dry weight	
Dimensions (mm)	



140 litres/min

25mm (1")-PF
36m
8m
3.6bar
5.7mm
0.55L
1h30 approx
6.1kg
L 325 × W 220 × H 300



240 litres/min

40mm (1.5")-PF
40m
8m
4bar
5.7mm
0.77L
1h30 approx
9kg
L 325 × W 275 × H 375



400 litres/min

40mm (1.5")-PF
50m
8m
5.0bar
3mm
2L
2h approx
22kg
L 415 × W 360 × H 405



500 litres/min

50mm (2")-PF
50m
8m
5.0bar
3mm
3.1L
2h30 approx
27kg
L 520 × W 400 × H 450

*Not available in the UK.
**Oil Alert™ option available.